

PART NO.	DIM A	DIM B	DIM C
M30-1400200	1.25	2.72	5.72
M30-1400300	2.50	3.97	6.97
M30-1400400	3.75	5.22	8.22
M30-1400500	5.00	6.47	9.47
M30-1400600	6.25	7.72	10.72
M30-1400700	7.50	8.97	11.97
M30-1400800	8.75	10.22	13.22
M30-1400900	10.00	11.47	14.47
M30-1401000	11.25	12.72	15.72
M30-1401100	12.50	13.97	16.97
M30-1401200	13.75	15.22	18.22
M30-1401400	16.25	17.72	20.72
M30-1401500	17.50	18.97	21.97
M30-1401600	18.75	20.22	23.22
M30-1402000	23.75	25.22	28.22
M30-1403000	36.25	37.72	40.72

SPECIFICATIONS:

MATERIAL:-

MOULDING: NYLON 66, UL94V-0

FINISH:-

MOULDING: BEIGE

ELECTRICAL:-

CURRENT RATING: 1.0 AMP

WORKING VOLTAGE: 125V AC/DC

WITHSTANDING VOLTAGE: 500V AC/MINUTE

CONTACT RESISTANCE: 20 mΩ MAX.

INSULATION RESISTANCE: 1000 MΩ MIN.

ENVIRONMENTAL:-

OPERATING TEMPERATURE: -25°C ~ +85°C


NOTES: ALL DIMENSIONS AND NOTES

MARKED * ARE CRITICAL AND

MUST BE CHECKED IN ACCORDANCE

WITH QUALITY DOC. QI-02A

Allan	2	17.09.07	A075
Allan	1	-	-
NAME	ISS.	DATE	C/NOTE

APPROVED: 

CHECKED:

DRAWN: Allan

ORDER CODE

M30-140 XX 00

NO. OF WAYS

CUSTOMER REF.:

ASSEMBLY DRG:

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.15mm
X.XXX = ±0.05mm
ANGLES = ±5°
UNLESS STATED

MATERIAL: SEE NOTES
FINISH: SEE NOTES
S/AREA: mm²

TITLE: 1.25mm PITCH HOUSING
DRAWING NUMBER: M30-140 XX 00

SHT
1
OF
1