



UNLESS OTHERWISE SPECIFIED:

1. TOLERANCES: FRACTIONS & 2 PLACE DECIMALS & .010
2. REMOVE ALL BURRS. BREAK SHARP EDGES .005 MAX.
3. PLACE DECIMALS & .004 ANGLES & 0° 30'
4. NO FILLETS PERMITTED.
5. SURFACE ROUGHNESS 49 MICROINCHES RMS MAX.
6. EXCEED HALF THE SUM OF THEIR TOLERANCES.
7. ALL DIMENSIONS PRIOR TO PLATING.

KC-79-238-706 (SHEET 10F2)

REVISIONS	
ISSUE	CHANGES
0	ER 18115 GA 10 MAR 78

SCALE 4:1	
S-D	
WAS E-7481	
USED ON:	
REV:	
FINISH:	
SPEC:	KER 10004
MATL:	
DRWING:	DATE 10 MAR 78
APPR:	DATE 10 MAR 78

KINGS ELECTRONICS
 48 MARSHDALE ROAD
 TUCKAHOE, N. Y. 10783

KC-79-238-706 (SHEET 10F2)

ITEM	REQ'D	DESCRIPTION	PART NO.
1	1	BODY	
2	1	INSULATOR	
3	1	BNC CONTACT F	
4	1	HEX NUT	C-79-57-4-M06
5	1	LOCKWASHER	492A-12-M06

ISSUE	REVISIONS
	CHANGES

S-D

USED ON:

REF:

FINISH

SPEC. KER 10004

MATL

SPEC:

PARTS LIST

DRAWN	M M	DATE	10 MAR 78
APPR.	<i>(Signature)</i>	DATE	13 MAR 78

KINGS ELECTRONICS

40 MARBLEDALE ROAD
TUCKAHOE, N. Y. 10707

KC-79-238-M06
(SHEET 2 OF 2)

- UNLESS OTHERWISE SPECIFIED:
1. TOLERANCES: FRACTIONS & 2 PLACE DECIMALS ± .010
 2. REMOVE ALL BURRS, BREAK SHARP EDGES .005 MAX.
 3. PLACE DECIMALS ± .004
 3. NO FILLETS PERMITTED.
 4. SURFACE ROUGHNESS 63 MICRONS RMS MAX.
 5. ALL DIMENSIONS PRIOR TO PLATING.
 - ANGLES ± OF 30°
 - T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED HALF THE SUM OF THEIR TOLERANCES.