


8.0×4.5mm for Automotive



RoHS Compliant

Features

- Crystal unit for automotive electronics
- Small and low profile (8.0×4.5×1.9mm)
- Ceramic package, J lead type
- Reflow compatible
- AEC-Q200 qualified

Applications

- ECU, TPMS

How to Order

CX8045JA 08000

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Stability
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification

DO	8 pF	—	P	$\pm 50 \times 10^{-6}$	—
HO	12 pF	Std.	Q	$\pm 100 \times 10^{-6}$	Std.

TW	-40 to +150°C	$\pm 200 \times 10^{-6}$	Std.
-----------	---------------	--------------------------	------

Packaging (Tape & Reel 3000/ 1000 pcs./ reel)

Specifications

Item	Symbol	Specification	Units	Remarks
Frequency Range	f _{nom}	4000 to 30000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	12	pF	
Frequency Stability	f _{tol}	±100	$\times 10^{-6}$	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T _{use}	-40 to +150	°C	
Storage Temp. Range	T _{stg}	-40 to +150	°C	
Frequency Temp. Characteristics	f _{tem}	±200	$\times 10^{-6}$	Freq. deviation from the value at 25°C

• Please contact us for other specifications.

Typical Frequencies and Part Numbers

Frequency (kHz)	Part Number
8000.000	CX8045JA08000H0QTWZ1
9843.750	CX8045JA09843H0QTWZ1
10000.000	CX8045JA10000H0QTWZ1
12000.000	CX8045JA12000H0QTWZ1
13560.000	CX8045JA13560H0QTWZ1
14000.000	CX8045JA14000H0QTWZ1
16000.000	CX8045JA16000H0QTWZ1
18000.000	CX8045JA18000H0QTWZ1
20000.000	CX8045JA20000H0QTWZ1
24000.000	CX8045JA24000H0QTWZ1
25000.000	CX8045JA25000H0QTWZ1
30000.000	CX8045JA30000H0QTWZ1

Table1 Motional Series Resistance


Frequency Range	Motional Series Resistance
4000 to 4999kHz	500Ω max.
5000 to 7199kHz	300Ω max.
7200 to 9999kHz	200Ω max.
10000 to 11999kHz	150Ω max.
12000 to 30000kHz	100Ω max.

Table2 Level of Drive

Frequency Range	Level of Drive
4000 to 15999kHz	10μW (500μW max.)
16000 to 24999kHz	10μW (300μW max.)
25000 to 30000kHz	10μW (100μW max.)

Dimensions

(Unit: mm)



Recommended Land Pattern

(Unit: mm)

