

Part Number: C0740A

Revision Level: 1

Date: 6/29/2007

2C 24 7/32 TC S-R PVC OAS PVC

COMPUTER CABLE

A. CONSTRUCTION

DIAMETERS

Conductor:	#24 AWG 7/32 Tinned Copper	0.024" nom.
Insulation:	0.010" Wall Semi-Rigid Polyvinyl Chloride	0.044" nom.
Cable:	2 Conductors @ 1.50" LHL - Aluminum/polyester (Foil Out) - #24 7/32 TC D.W.	0.093" nom.
Jacket:	0.032" Polyvinyl Chloride	0.157" +/- 0.008"
Print Legend:	CAROL (R) 24 AWG -- C0740A -- 75C E111240-8 CMR (UL)C(UL) OR 80C AWM STYLE 2464 300V --- CSA LL69381 CMG -- MADE IN USA (Date Code MM/YY)	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CMR
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C (CMR) / 80C (2464) / 60C (CMG)
SUGGESTED WORKING VOLTAGE (Vrms):	300 Vrms
CONDUCTOR D.C. RESISTANCE:	26 Ohms/1000 ft nom
SHIELD RESISTANCE:	7.2 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	35.83 pF/ft @ 1kHz nom
GROUND CAPACITANCE:	64.49 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	53.8 Ohms @ 1MHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White