



NOTES:

1. FOR USE WITH BOEING BMS13-65 OG & ADAMS RUSSELL FC20Z CABLES.
2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
3. FOR CRIMPING USE DIE KTH-2231.
4. INTERFACE PER MIL-STD-348, FIG. 304-2.
5. CENTER CONTACT (1-534-98MA9) SUPPLIED UNASSEMBLED.
6. MARK PACKAGE: KINGS 1203-19-9 (DATE CODE)
7. MATERIALS:
 INSULATOR: TEFLON, ASTM D1710
 K-GRIP SLEEVE: COM. BRONZE, ASTM B135
 CENTER CONTACT: BERYLLIUM COPPER, ASTM B196
 ALL OTHER PARTS: BRASS, ASTM B16
8. FINISHES:
 CENTER CONTACT: .000050 MIN GOLD PLATE PER ASTM B488 OVER .000050 MIN NICKEL PER ASM-QQ-N-290 (RoHS)
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PER ASM-QQ-N-290 OVER .000050 COPPER PER ASTM B734 (RoHS)
9. ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 50 OHMS
 VOLTAGE RATING: 1000 VRMS
 FREQUENCY RANGE: DC TO 11 GHz
10. WEIGHT: 33.4 GRAMS

1203-19-9

REVISIONS	
ISSUE	CHANGES
1	ADD LOCK WIRE HOLES KH 04/26/94
2	ER 35916 MJB 12/07/94
D	REVISED PER DMF304 & ER34618 KPL 08/26/11

CUSTOMER
SALES
DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

WAS: E-18630

CAGE CODE: 91836

REF: BOEING

JACK, N

DRAWN KH DATE 03/15/94

DESIGN JT DATE 03/16/94

APPR. DATE

WINCHESTER
ELECTRONICS
Winchester Electronics Corporation
62 Barnes Industrial Road North
Wallingford, Connecticut 06492

1203-19-9