

Part Number: C0766A

Revision Level: 1

Date: 7/10/2007

15C 22 7/30 TC S-R PVC OAS PVC

COMPUTER CABLE

A. CONSTRUCTION

Conductor:	#22 AWG 7/30 Tinned Copper	0.029" nom.
Insulation:	0.010" Wall Semi-Rigid Polyvinyl Chloride	0.049" nom.
Cable:	15 Conductors @ 3.50" LHL - Aluminum/polyester (Foil Out) - #22 7/30 TC D.W.	0.240" nom.
Jacket:	0.032" Polyvinyl Chloride	0.304" +/- 0.015"
Print Legend:	CAROL (R) 22 AWG -- C0766A -- 75C E111240-8 CMR (UL)C(UL) OR 80C AWM STYLE 2464 300V --- CSA LL69381 CMG -- MADE IN USA	

DIAMETERS

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CMR
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C (CMR) / 80C (2464) / 60C (CMG)
SUGGESTED WORKING VOLTAGE (Vrms):	300 Vrms
CONDUCTOR D.C. RESISTANCE:	16.5 Ohms/1000 ft nom
SHIELD RESISTANCE:	6.3 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	33.02 pF/ft @ 1kHz nom
GROUND CAPACITANCE:	59.44 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	52.5 Ohms @ 1MHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black	11	Blue / Black
2	White	12	Black / White
3	Red	13	Red / White
4	Green	14	Green / White
5	Orange	15	Blue / White
6	Blue		
7	White / Black		
8	Red / Black		
9	Green / Black		
10	Orange / Black		