

F35 UK Wall Mount 1-3 Watts Series

Features

- 230 VAC Input
- UK Wall Plug Style
- Rated for Continuous Duty
- Filtered
- Unregulated Outputs up to 3 Watts
- Meets Safety Agency Requirements
- CE Compliant
- Impact Resistant Polycarbonate Enclosure
- Private Label Marking Available
- 1 Year Warranty
- Modified and Custom Designs Also Available
- Manufactured in China

Ault Model	Rated Output Volts DC	Maximum Current-Amps	Maximum Watts
F35-050400-A000G	5	0.40	2.0
F35-060200-A000G	6	0.20	1.2
F35-060300-A000G	6	0.30	1.8
F35-060400-A000G	6	0.40	2.4
F35-080250-A000G	8	0.25	2.0
F35-090100-A000G	9	0.10	0.9
F35-100300-A000G	10	0.30	3.0
F35-110273-A000G	11	0.30	3.0
F35-120200-A000G	12	0.20	2.4
F35-140214-A000G	14	0.21	3.0
F35-150150-A000G	15	0.15	2.3
F35-180167-A000G	18	0.17	3.0
F35-200150-A000G	20	0.15	3.0
F35-210143-A000G	21	0.14	3.0
F35-220136-A000G	22	0.14	3.0
F35-240125-A000G	24	0.13	3.0

Input

- Voltage 230 VAC
- Line Frequency 50 Hz
- Connector UK Wall Plug, No Ground

Electrical

- Topology DC Unregulated Power Supply
- Dielectric Withstand 3000 VAC primary-secondary
1500 VAC primary-core
500 VAC secondary-core
- Protection Current, Thermal or Energy Limiting
- EMI Complies with EMC Directives
- CE CE Compliant

Safety Approvals

- Safety Agencies EN60950 or EN60742

Environmental

- Operating Temperature 5° to 40° C with no derating
- Storage Temperature -30° to +85° C
- Relative Humidity 5% to 95% non-condensing
- Altitude 0-10,000 feet
- Cooling Convectional - non vented case

Mechanical

- Case Dimensions F35 - UK Wall Plug
2.3 L x 1.8 W x 1.7 H (in)
59 L x 45 W x 42 H (mm)
- Case Material Black 94 V1 Polycarbonate
- Weight 8 ounces, 220 grams,
(excluding cord)
- Cord and Connector 6 ft., 2 Conductor, 22-24 AWG
Ault #3 Connector
Other Connectors Available

ONE YEAR WARRANTY

Ault Incorporated, 7105 Northland Terrace, Minneapolis, MN 55428

Contact Ault Inc. for all your custom design requirements. Phone: 763.592.1900 · Fax 763.592.1911