





PRODUCT SPECIFICATION

DATE : 02/22/2011



COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQV216A	NO.61M10025	REV. 4
		SHEET 1 OF 7	

● OUTSIDE DIMENSION :



Unit : mm
Tolerance : ±0.2mm

● Turn On / Turn Off time



● Absolute Maximum Ratings

(Ta=25°C)

Emitter (Input)	Detector (Output)
Reverse Voltage 5.0V	Output Breakdown Voltage ± 600V
Continuous Forward Current 50mA	Continuous Load Current ± 120mA
Peak Forward Current 1A	Power Dissipation 500mW
Power Dissipation 100mW	
Derate Linearly from 25°C 1.3mW/°C	

General Characteristics

Isolation Test Voltage 5000VACrms	Storage Temperature Range -40°C to +125°C
Isolation Resistance Vio=500V, Ta=25°C $\geq 10^{10}\Omega$	Operating Temperature Range ... -40°C to +85°C
Total Power Dissipation 550mW	Junction Temperature 100°C
Derate Linearly from 25°C 2.5mW/°C	Soldering Temperature , 2mm from case , 10 sec 260°C

PRODUCT SPECIFICATION

DATE : 02/22/2011

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQV216A	NO.61M10025	REV. 4
		SHEET 2 OF 7	

● Electro-optical Characteristics

(Ta=25°C)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit.
Emitter (Input)						
Forward Voltage	V_F	$I_F=10\text{mA}$		1.2	1.5	V
Operation Input Current	$I_{F\text{ON}}$	$V_L=\pm 20\text{V}$, $I_L=100\text{mA}$, $t=10\text{mS}$			5.0	mA
Recovery Input Current	$I_{F\text{OFF}}$	$V_L=\pm 20\text{V}$, $I_L \leq 5\mu\text{A}$	0.2			mA
Detector (Output)						
Output Breakdown Voltage	V_B	$I_B=50\mu\text{A}$	600			V
Output Off-State Leakage	$I_{T\text{OFF}}$	$V_T=600\text{V}$, $I_F=0\text{mA}$		0.2	1	μA
I/O Capacitance	C_{ISO}	$I_F=0$, $f=1\text{MHz}$		6		pF
ON Resistance	Connection	R_{ON}	$I_L=100\text{mA}$, $I_F=10\text{mA}$	35	80	Ω
				27	40	
				15	20	
Turn-On Time	T_{ON}	$I_F=10\text{mA}$, $V_L=\pm 20\text{V}$ $t=10\text{ms}$, $I_L=\pm 100\text{mA}$		0.3	1.0	ms
Turn-Off Time	T_{OFF}			0.5	1.5	ms

● Schematic and Wiring Diagrams

Schematic	Output configuration	Load	Connection	Wiring Diagrams
	1a	AC/DC	A	
			B	
			C	

PRODUCT SPECIFICATION

DATE : 02/22/2011


COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQV216A	NO.61M10025	REV. 4
		SHEET 3 OF 7	

● Data Curve

Load current vs. ambient temperature

Allowable ambient Temperature :

-40°C to +85°C




Ambient temperature Ta (°C)

On resistance vs. ambient temperature across terminals 4 and 6 pin

LED current : 5mA

Continuous load current : 120mA (DC)




Ambient temperature Ta (°C)

Turn On Time vs. ambient temperature

Load voltage 600V (DC)

LED current : 5mA

Continuous load current : 120mA (DC)




Ambient temperature Ta (°C)

Turn Off Time vs. ambient temperature

Load voltage 600V (DC)

LED current : 5mA

Continuous load current : 120mA (DC)




Ambient temperature Ta (°C)

PRODUCT SPECIFICATION

DATE : 02/22/2011


COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQV216A	NO.61M10025	REV. 4
		SHEET 4 OF 7	

LED operate current vs.
ambient temperature
Load Voltage : 600V (DC)
Continuous load current : 120mA (DC)




Ambient temperature Ta (°C)

LED Turn Off current vs.
ambient temperature
Load Voltage : 600V (DC)
Continuous load current : 120mA (DC)




Ambient temperature Ta (°C)

LED dropout voltage vs.
ambient temperature
LED current : 5 to 50mA



Ambient temperature Ta (°C)

Voltage vs. current characteristics
of output at MOSFET portion
Measured portion : across terminals
4 and 6 pin
Ambient temperature : 25°C



Ambient temperature : 25°C

PRODUCT SPECIFICATION

DATE : 02/22/2011

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQV216A	NO.61M10025	REV. 4
		SHEET 5 OF 7	


LED forward current vs. Turn On Time

Across terminals 4 and 6pin

Load voltage : 600V (DC)

Continuous load current : 120mA (DC)

Ambient temperature : 25°C




LED forward current (mA)

Off state leakage current

Across terminals 4 and 6 pin

Ambient temperature : 25°C



Load voltage (V)


LED forward current vs. reverse(ON) time

Across terminals 4 and 6 pin

Load voltage : 600V (DC)

Continuous load current : 120mA (DC)

Ambient temperature : 25°C




LED forward current (mA)

Applied voltage vs. output capacitance

Across terminals 4 and 6 pin

Frequency : 1MHz

Ambient temperature : 25°C



Applied voltage (V)

PRODUCT SPECIFICATION

DATE : 02/22/2011


COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY - MOSFET OUTPUT KAQV216A	NO.61M10025	REV. 4
		SHEET 6 OF 7	

● USING METHODS

Examples of resistance value to control LED forward current (IF)


SSR-MOSFET OUTPUT

(IF=5mA)



E	R
3.3V	Approx. 330 Ω
5V	Approx. 640 Ω
12V	Approx. 1.9K Ω
15V	Approx. 2.5K Ω
24V	Approx. 4.1K Ω

- (1) LED forward current must be more than 5mA , at E min.
- (2) LED forward current must be less than 50mA , at E max.



PRODUCT SPECIFICATION

DATE : 02/22/2011

COSMO
ELECTRONICS CORPORATION



SOLID STATE RELAY - MOSFET OUTPUT
KAQV216A

NO.61M10025
SHEET 7 OF 7

REV.
4

● USING METHODS

Regulate the spike voltage generated on the inductive load as follows :



R-C Snubber