

16 AMP SUPER-EFFICIENT RECTIFIERS

FEATURES

- Glass Passivated for high reliability/temperature performance
- Low switching noise
- Low forward voltage drop
- Low thermal resistance
- High switching capability
- High surge capability


RoHS COMPLIANT

MECHANICAL DATA


- Case: TO-220 molded epoxy (U/L Flammability Rating 94V-0)
- Terminals: Rectangular pins w/ standoff
- Solderability: Per MIL-STD 202 Method 208 guaranteed
- Polarity: Diode depicted on product
- Mounting Position: Any
- Weight: 0.08 Ounces (2.2 Grams)

MECHANICAL SPECIFICATION

ACTUAL SIZE OF TO-220AB PACKAGE



NON - INSULATED PACKAGE



Sym	Minimum		Maximum	
	in	mm	in	mm
A			0.187	4.75
A1	0.055*	1.4*		
A2	0.14*	3.56*		
B	0.035	0.9	0.043	1.1
B1	0.09	2.3	0.102	2.6
B2	0.029*	0.66*		
B3	0.051*	1.3*		
C			0.410	10.4
D	0.59	15.0	0.61	15.5
D1	0.25*	6.4*		
D2			0.16	4.0
D3	0.53	13.5	0.57	14.8
D4	0.108*	2.75*		
P	0.141*	3.58*		

* These dimensions are "Typicals".

TO - 220AB

SERIES SPR161C - SPR166C


MAXIMUM RATINGS & ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
 Single phase, half wave, 60Hz, resistive or inductive load.
 For capacitive loads, derate current by 20%.

PARAMETER (TEST CONDITIONS)	SYMBOL	RATINGS						UNITS
		SPR 161C	SPR 162C	SPR 163C	SPR 164C	SPR 165C	SPR 166C	
Series Number								
Maximum DC Blocking Voltage	V _{RM}	100	200	300	400	500	600	VOLTS
Maximum RMS Voltage	V _{RMS}	70	140	210	280	350	420	
Maximum Peak Recurrent Reverse Voltage	V _{RRM}	100	200	300	400	500	600	
Average Forward Rectified Current @ T _c = 100 °C	I _O	16						AMPS
Peak Forward Surge Current (8.3mS single half sine wave superimposed on rated load)	I _{FSM}	200						
Maximum Forward Voltage at 8 Amps DC	V _{FM}	0.975	1.3		1.5			VOLTS
Maximum Average DC Reverse Current @ T _c = 25 °C At Rated DC Blocking Voltage @ T _c = 100 °C	I _{RM}	10				500		μA
Typical Thermal Resistance, Junction to Case	R _{θJC}	3						°C/W
Typical Junction Capacitance (Note 1)	C _J	65						pF
Maximum Reverse Recovery Time (I _F =0.5A, I _R =1.0A, I _{RR} =0.25A)	T _{RR}	35		50				nSec
Junction Operating and Storage Temperature Range	T _J , T _{STG}	-65 to +150						°C

NOTES: (1) Measured at 1 MHz and an applied reverse voltage of 4 volts.

4370ed916c



16 AMP SUPER EFFICIENT RECTIFIERS

RATING & CHARACTERISTIC CURVES FOR SERIES SPR161C - SPR166C




FIGURE 1. FORWARD CURRENT DERATING CURVE




FIGURE 2. MAXIMUM NON-REPETITIVE SURGE CURRENT




FIGURE 3. TYPICAL FORWARD CHARACTERISTICS




FIGURE 4. TYPICAL REVERSE CHARACTERISTICS




FIGURE 5. TYPICAL JUNCTION CAPACITANCE

NOTES

- (1) JEDEC Method, 8.3 mSec. Single Half Sine Wave
- (2) $T_J = 25^\circ\text{C}$, Pulse Width = 300 μSec , 2.0% Duty Cycle
- (3) $T_J = 25^\circ\text{C}$