

Part Number: C1704

Revision Level: 11/19/2012

2C 16AWG 26/30BC PP, PVC
COMMAND® SERIES
A. CONSTRUCTION

| | | |
|---------------|---|-------------------------|
| Conductor: | 16 AWG 26/30 BC | <u>DIAMETERS</u> |
| Insulation: | .009" Wall, Polypropylene (PP) | .057" nom |
| Cable Core: | 2C @ 6.00" LHL | .075" nom |
| Jacket: | .030" Polyvinyl Chloride (PVC) | .150" nom |
| Print Legend: | CAROL® -- C1704 -- 2C 16AWG COMMAND SERIES AUDIO CABLE (UL) E60233-8 CL3 60C -- CSA C/US CMG 80C OR CSA AWM I/II A/B 80C 600V FT4 -- ROHS -- MADE IN USA (Date code) (Seq Footage) | |

B. INDUSTRY APPROVALS

| | |
|--------------------------|-------------------|
| National Electrical Code | Article 725 |
| UL Standard 444 | Type CL3 |
| CSA International | Type AWM I/II A/B |

C. ELECTRICAL PROPERTIES

| | |
|----------------------------|---------------------------|
| Temperature: | -20°C to +80°C |
| Suggested Working Voltage: | 600V Max |
| Conductor DCR: | 4.03 Ohms/M' @ 20°C (nom) |
| Mutual Capacitance: | 21.4 pF/ft @ 1kHz (nom) |

D. COLOR CODE

| Item | COLOR |
|------|-------|
| 1 | BLACK |
| 2 | RED |

E. CUSTOMER APPROVAL

Signature: _____
 Date: _____