



## SPECIFICATIONS

FREQUENCY RANGE: 1.0–2.0 GHz  
 COUPLING (INCLUDES FREQUENCY SENSITIVITY):  $20 \pm 1.25$  dB  
 FREQUENCY SENSITIVITY:  $\pm 0.75$  dB  
 INSERTION LOSS: (EXCLUDING COUPLED POWER) 0.15 dB (TRUE) 0.20 dB  
 DIRECTIVITY: 25 dB MINIMUM  
 PRIMARY LINE: 1.10 VSWR MAX.  
 SECONDARY LINE: 1.10 VSWR MAX.  
 AVG. INCIDENT: 50 WATTS POWER  
 AVG. REFLECTED: 50 WATTS POWER  
 PEAK: 3 KW POWER



**PASTERNAK ENTERPRISES, INC.**

P.O. BOX 16759, IRVINE, CA 92623  
 PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: [www.pasternack.com](http://www.pasternack.com)  
 E-MAIL ADDRESS: [sales@pasternack.com](mailto:sales@pasternack.com)

**COAXIAL & FIBER OPTICS**

DWG TITLE

**PE2201-20**

DES. SMA FEMALE DIRECTIONAL COUPLER,  
 FREQUENCY RANGE: 1-2 GHz

REV. A **FSCM NO. 53919**

CAD FILE 092908

SCALE N/A

SIZE A 147

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.