TOSHIBA Transistor Silicon NPN Epitaxial Planar Type

2SC5087


VHF~UHF Band Low Noise Amplifier Applications

Unit: mm

- Low noise figure, high gain.
- NF = 1.1dB, $|S_{21e}|^2 = 13dB$ (f = 1 GHz)

Maximum Ratings (Ta = 25°C)

Characteristics	Symbol	Rating	Unit	
Collector-base voltage	V_{CBO}	20	V	
Collector-emitter voltage	V _{CEO}	12	V	
Emitter-base voltage	V _{EBO}	3	V	
Base current	ΙΒ	40	mA	
Collector current	I _C	80	mA	
Collector power dissipation	PC	150	mW	
Junction temperature	Tj	125	°C	
Storage temperature range	T _{stg}	-55~125	°C	



Weight: 0.012 g (typ.)

Microwave Characteristics (Ta = 25°C)

Characteristics	Symbol	Test Condition	Min	Тур.	Max	Unit	
Transition frequency	f _T	$V_{CE} = 10 \text{ V}, I_{C} = 20 \text{ mA}$	5	7	_	GHz	
Insertion gain	S _{21e} ² (1)	$V_{CE} = 10 \text{ V}, I_{C} = 20 \text{ mA}, f = 500 \text{ MHz}$		18		dB	
mseriion gain	S _{21e} ² (2)	V _{CE} = 10 V, I _C = 20 mA, f = 1 GHz	9.5	13	_	ub	
Noise figure	NF (1)	$V_{CE} = 10 \text{ V}, I_{C} = 5 \text{ mA}, f = 500 \text{ MHz}$		1		dB	
Noise ligure	NF (2)	$V_{CE} = 10 \text{ V}, I_{C} = 5 \text{ mA}, f = 2 \text{ GHz}$		1.1	2	T UD	


Electrical Characteristics (Ta = 25°C)

Characteristics	Symbol	nbol Test Condition		Тур.	Max	Unit
Collector cut-off current	I _{CBO}	$V_{CB} = 10 \text{ V}, I_{E} = 0$	_	_	1	μΑ
Emitter cut-off current	I _{EBO}	V _{EB} = 1 V, I _C = 0	_	_	1	μΑ
DC current gain	h _{FE} (Note 1)	V _{CE} = 10 V, I _C = 20 mA	80	_	240	
Output capacitance	C _{ob}	V _{CB} = 10 V, I _E = 0, f = 1 MHz (Note 2)	_	1.1	1.6	pF
Reverse transfer capacitance	C _{re}	$V_{CR} = 10 \text{ V}, 1E = 0, 1 = 1 \text{ INITZ} (NOTE 2)$	_	0.65	1.05	pF


Note 1: hFE classification O: 80~160, Y: 120~240


Note 2: C_{re} is measured by 3 terminal method with capacitance bridge.


Marking





2 2003-03-19
















3





S-Parameter $Z_O = 50 \Omega$, Ta = 25°C

$V_{CE} = 10 \text{ V}, I_C = 5 \text{ mA}$

Frequency	S11		S21		S12		S22	
MHz	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.
200	0.793	-82.4	11.923	133.4	0.050	52.7	0.788	-36.4
400	0.736	-128.0	7.835	108.5	0.066	38.0	0.584	-53.4
600	0.719	-152.1	5.578	94.5	0.071	34.1	0.490	-63.5
800	0.701	-168.6	4.279	84.4	0.073	33.9	0.445	-72.2
1000	0.698	178.9	3.451	76.6	0.074	36.7	0.424	-80.5
1200	0.697	168.3	2.855	69.9	0.076	40.8	0.413	-88.9
1400	0.699	159.4	2.440	64.0	0.078	46.6	0.404	-97.3
1600	0.703	150.8	2.121	59.3	0.084	52.5	0.401	-105.4
1800	0.713	142.9	1.876	54.5	0.091	58.3	0.398	-112.6
2000	0.722	134.7	1.681	50.3	0.100	63.5	0.398	-119.6


$V_{CE} = 10 \text{ V}, I_C = 20 \text{ mA}$


Frequency	S11		S21		S12		S22	
MHz	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.
200	0.655	-129.4	20.724	113.2	0.031	48.0	0.496	-59.6
400	0.650	-161.5	11.288	95.5	0.040	50.4	0.319	-74.1
600	0.660	-176.3	7.643	86.4	0.049	56.4	0.263	-83.5
800	0.666	172.8	5.758	79.6	0.059	60.0	0.242	-92.9
1000	0.667	164.0	4.605	74.2	0.070	63.6	0.233	-102.0
1200	0.668	156.8	3.809	69.3	0.080	65.9	0.229	-111.0
1400	0.677	148.4	3.277	65.1	0.091	68.2	0.226	-119.1
1600	0.676	141.1	2.862	61.2	0.104	70.0	0.223	-126.5
1800	0.688	133.9	2.559	57.5	0.117	71.2	0.220	-132.4
2000	0.690	126.7	2.303	54.1	0.131	72.4	0.217	-137.8

4 2003-03-19


 $\begin{array}{l} S_{11e} \\ V_{CE} = 10V \\ I_{C} = 5 \text{mA} \\ Ta = 25 ^{\circ}\text{C} \\ (Unit: \Omega) \end{array}$








 $\begin{array}{l} S_{12e} \\ V_{CE} = 10V \\ I_{C} = 5 mA \\ Ta = 25 ^{\circ}C \end{array}$





 $\begin{array}{l} S_{22e} \\ V_{CE} = 10V \\ I_{C} = 5 \text{mA} \\ T_{a} = 25 ^{\circ}\text{C} \\ \text{(Unit : } \Omega\text{)} \end{array}$




 $\begin{array}{l} S_{11e} \\ V_{CE} = 10V \\ I_{C} = 20 mA \\ Ta = 25 ^{\circ}C \\ (Unit: \Omega) \end{array}$








 $\begin{array}{l} \mathrm{S}_{12e} \\ \mathrm{V}_{CE} \!=\! 10\mathrm{V} \\ \mathrm{I}_{C} \!=\! 20\mathrm{mA} \\ \mathrm{Ta} \!=\! 25^{\circ}\!\mathrm{C} \end{array}$



 $\begin{array}{l} S_{22e} \\ V_{CE} = 10V \\ I_{C} = 20 mA \\ T_{a} = 25 ^{\circ}C \\ (Unit: \Omega) \end{array}$



RESTRICTIONS ON PRODUCT USE

000707EAA

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
 In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The information contained herein is presented only as a guide for the applications of our products. No
 responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other
 rights of the third parties which may result from its use. No license is granted by implication or otherwise under
 any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.