



RECOMMENDED HOLE LAYOUT

1. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD.
2. THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
3. POINT OF MEASUREMENT FOR PLATING THICKNESS.
4. OBSOLETE PART NUMBER.
5. RETENTION FEATURES ON SOLDER TAILS, LOCATED AT MANUFACTURERS OPTION.
6. FOR 2 POSITION PART ONLY, THE NOTED DIMENSION IS .184
7. $\text{M} \text{ } \phi .020$ FOR KINKED TAILS
8. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OBSOLETE	3.284	3.200	32	66	2-104433-4
	1.784	1.700	17	36	2-104433-3
	3.484	3.400	34	70	2-104433-2
	2.184	2.100	21	44	2-104433-1
	3.984	3.900	39	80	2-104433-0
	2.484	2.900	29	60	1-104433-9
	2.484	2.400	24	50	1-104433-8
	1.984	1.900	19	40	1-104433-7
OBSOLETE	1.684	1.600	16	34	1-104433-6
	1.484	1.400	14	30	1-104433-5
	1.384	1.300	13	28	1-104433-4
	1.284	1.200	12	26	1-104433-3
OBSOLETE	1.184	1.100	11	24	1-104433-2
	1.084	1.000	10	22	1-104433-1
	.984	.900	9	20	1-104433-0
	.884	.800	8	18	1-104433-9
OBSOLETE	.784	.700	7	16	1-104433-8
	.684	.600	6	14	1-104433-7
	.584	.500	5	12	1-104433-6
	.484	.400	4	10	1-104433-5
	.384	.300	3	8	1-104433-4
	.284	.200	2	6	1-104433-3
	.184	.100	1	4	1-104433-2
	.084	—	—	2	1-104433-1
C	B	A	NO OF POSN	ASSEMBLY PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	H MOLL	23JUN88	 TE Connectivity
DIMENSIONS: INCHES		CHK	R FEJDT	23JUN88	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	R FEJDT	23JUN88	NAME
0. PLC	± -	PRODUCT SPEC			HEADER ASSY, MOD II,
1. PLC	± -	APPLICATION SPEC			BREAKAWAY, DBL ROW, 100X.100 C
2. PLC	± -	WEIGHT			VERT. .025 SQ POSTS, WITH RETENTION FEATURE
3. PLC	± .005	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
4. PLC	± -	A1	00779	104433	
ANGLES	± -	CUSTOMER DRAWING			SCALE 4:1 SHEET 1 of 1 REV P2