



**ELECTRONICS, INC.**  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089

## NTE704 Integrated Circuit TV Sound, IF Amp

### Features & Applications:

- Exceptionally High Gain: Power Gain at 4.5Hz – 75dB typ.
- Excellent Limiting Characteristics: Input Limiting Voltage (Knee) = 300µV at 4.5MHz
- Excellent AM Rejection: > 50dB at 4.5MHz
- High Audio–Voltage Recovery: 20mV Typ at 4.5MHz, 25kHz Deviation
- Wide Frequency Capability: 100kHz to > 20MHz
- Comprehensive Circuit Functions:
  - IF Amplifier
  - AM and Noise Limiter
  - FM Detector
  - Audio PreAmplifier

### Absolute Maximum Ratings: ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Maximum Input–Signal Voltage (Between Pin1 and Pin2) .....	±3V
Maximum Device Dissipation .....	300mW
Recommended Minimum DC Supply Voltage ( $V_{CC}$ ) .....	5.5V
Operating Temperature Range, $T_{opr}$ .....	–55° to +125°C
Storage Temperature Range, $T_{stg}$ .....	–65° to +150°C

### Electrical Characteristics: ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
Total Device Dissipation	$P_T$	Note 1	$V_{CC} = 6V$	73	90	110	mW
			$V_{CC} = 7.5V$	106	120	150	mW
			$V_{CC} = 10V$	165	190	230	mW
Voltage Gain	A	f = 1Mc/s, Note 2	$V_{CC} = 6V$	60	66	–	dB
			$V_{CC} = 7.5V$	65	70	–	dB
			$V_{CC} = 10V$	65	71	–	dB
		$V_{CC} = 7.5V$ , Note 2	f = 4.5Mc/s	60	67	–	dB
			f = 10.7Mc/s	55	60	–	dB

Note 1. Total current drain may be determined by dividing  $P_T$  by  $V_{CC}$ .

Note 2. Recommended minimum DC supply voltage ( $V_{CC}$ ) is 5.5V. Nominal load current flowing into Pin5 is 1.5mA at 7.5V.

**Electrical Characteristics (Cont'd):** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Parallel Input Resistance	$R_{IN}$	$f = 4.5\text{Mc/s}, V_{CC} = 7.5\text{V}$	–	3	–	$\text{k}\Omega$
Parallel Input Capacitance	$C_{IN}$		–	7	–	$\text{pF}$
Parallel Output Resistance	$R_{OUT}$	$f = 4.5\text{Mc/s}, V_{CC} = 7.5\text{V}$	–	31.5	–	$\text{k}\Omega$
Parallel Output Capacitance	$C_{OUT}$		–	4.2	–	$\text{pF}$
Noise Figure	NF	$f = 4.5\text{Mc/s}, V_{CC} = 7.5\text{V}$	–	8.7	–	dB
Input Limiting Voltage (Knee)	$V_{i(lim)}$	$f = 4.5\text{Mc/s}, V_{CC} = 7.5\text{V}$	–	300	400	$\mu\text{V}$
Recovered AF	$V_{o(af)}$	$f = 4.5\text{Mc/s}$ $V_{CC} = 6\text{V}$	–	155	–	mV
		$V_{CC} = 7.5\text{V}$	135	188	–	mV
		$V_{CC} = 10\text{V}$	–	220	–	mV
Amplitude Modulation Rejection	AMR	$f = 4.5\text{Mc/s}, V_{CC} = 7.5\text{V}$	–	50	–	dB
Discriminator Output Resistance	$R_{O(dics)}$	$f = 4.5\text{Mc/s}, V_{CC} = 7.5\text{V}$	–	60	–	$\Omega$
Total Harmonic Distortion	THD	$f = 4.5\text{Mc/s}, V_{CC} = 7.5\text{V}$	–	1.8	–	%

**Pin Connection Diagram**  
(Top View)

