

Hermetically Sealed BNC Female to BNC Female Bulkhead Adapter For 1 inch Max. Panel



**PE9420** 

# **TECHNICAL DATA SHEET**

### Hermetically Sealed BNC Female to BNC Female Bulkhead Adapter For 1 inch Max. Panel

## Configuration

Connector 1 Impedance 1 Connector 2 Impedance 2 Adapter Design Body Style Mount Method Isolated Ground / Hermetic

### **Mechanical Specifications**

**Size** Length, in [mm] Width/Dia., in [mm]

#### **Connector 1**

Type Inner Conductor Material and Plating Body Material and Plating Dielectric Type

#### Connector 2

Type Inner Conductor Material and Plating Body Material and Plating Dielectric Type 50 Ohms BNC Female 50 Ohms Standard Straight Bulkhead Hermetically Sealed

**BNC** Female

2.282 [57.96] 0.687 [17.45]

BNC Female Silver Brass, Nickel PTFE

BNC Female Silver Brass, Nickel PTFE

Compliance Certifications (visit www.Pasternack.com for current document) RoHS Compliant Yes

#### Plotted and Other Data

Notes:

Values at 25 °C, sea level

URL: http://www.pasternack.com/bnc-female-bnc-female-straight-adapter-pe9420-p.aspx

Hermetically Sealed BNC Female to BNC Female Bulkhead Adapter For 1 inch Max. Panel from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



1

PE9420 CAD Drawing Hermetically Sealed BNC Female to BNC Female Bulkhead Adapter For 1 inch Max. Panel

