

# Precision N Male to N Male Adapter



### **TECHNICAL DATA SHEET**

**PE9427** 

#### Precision N Male to N Male Adapter

Configuration

Connector 1 N Male
Connector 2 N Male
Adapter Design Precision
Body Style Straight

**Electrical Specifications** 

Frequency Range, GHz
Impedance, Ohms
50
Maximum VSWR
1.15:1

## **Mechanical Specifications**

Size

 Length, in [mm]
 1.872 [47.55]

 Width/Dia., in [mm]
 0.8 [20.32]

 Dielectric Type
 Oxide-Noryl

**Connector 1** 

Type N Male

Inner Conductor Material and Plating
Inner Conductor Plating Specification

Beryllium Copper, Gold
MIL-G-45204

Body Material and Plating Stainless Steel, Passivated

Body Plating Specification ASTM A380

Connector 2

Type N Male

Inner Conductor Material and Plating Beryllium Copper, Gold

Inner Conductor Plating Specification MIL-G-45204

Body Material and Plating Stainless Steel, Passivated

Body Plating Specification ASTM A380

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/n-male-n-male-straight-adapter-pe9427-p.aspx

Precision N Male to N Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

# PE9427 CAD Drawing

Precision N Male to N Male Adapter

