


Type 8113 S/...WF Type 8213 S/...WF

spacing 5/ 5.00mm

Horizontal socket

plug-in parallel to PC board



8113 S/...WF part no

marked

25.339.0253.1
25.339.0353.1
25.339.0453.1

25.339.0553.1
25.339.0653.1
25.339.0753.1

25.339.0853.1
25.339.0953.1
25.339.1053.1

25.339.1153.1
25.339.1253.1
25.339.1353.1

25.339.1453.1
25.339.1553.1
25.339.1653.1

25.339.1753.1
25.339.1853.1
25.339.1953.1

25.339.2053.1
25.339.2153.1
25.339.2253.1

5mm pin spacing part no

unmarked

25.339.3253.1
25.339.3353.1
25.339.3453.1

25.339.3553.1
25.339.3653.1
25.339.3753.1

25.339.3853.1
25.339.3953.1
25.339.4053.1

25.339.4153.1
25.339.4253.1
25.339.4353.1

25.339.4453.1
25.339.4553.1
25.339.4653.1

25.339.4753.1
25.339.4853.1
25.339.4953.1

25.339.5053.1
25.339.5153.1
25.339.5253.1

8213 S/...WF part no

marked

25.358.0253.0
25.358.0353.0
25.358.0453.0

25.358.0553.0
25.358.0653.0
25.358.0753.0

25.358.0853.0
25.358.0953.0
25.358.0053.0

25.358.0153.0
25.358.0253.0
25.358.0353.0

25.358.0453.0
25.358.0553.0
25.358.0653.0

25.358.0753.0
25.358.0853.0
25.358.0953.0

25.358.2053.0
25.358.2153.0
25.358.2253.0

5.00mm pin spacing part no

unmarked

25.358.3253.0
25.358.3353.0
25.358.3453.0

25.358.3553.0
25.358.3653.0
25.358.3753.0

25.358.3853.0
25.358.3953.0
25.358.4053.0

25.358.4153.0
25.358.4253.0
25.358.4353.0

25.358.4453.0
25.358.4553.0
25.358.4653.0

25.358.4753.0
25.358.4853.0
25.358.4953.0

25.358.5053.0
25.358.5153.0
25.358.5253.0

Z5.523.2453.0

Z5.523.2453.0

Type 8113 S/..GF Type 8213 S/..GF

spacing 5/5.00 mm

Vertical socket

plug-in perpendicular to PC board



8113 S/..GF part no

marked

25.338.0253.1
25.338.0353.1
25.338.0453.1

25.338.0553.1
25.338.0653.1
25.338.0753.1

25.338.0853.1
25.338.0953.1
25.338.1053.1

25.338.1153.1
25.338.1253.1
25.338.1353.1

25.338.1453.1
25.338.1553.1
25.338.1653.1

25.338.1753.1
25.338.1853.1
25.338.1953.1

25.338.2053.1
25.338.2153.1
25.338.2253.1

5mm pin spacing part no

unmarked

25.338.3253.1
25.338.3353.1
25.338.3453.1

25.338.3553.1
25.338.3653.1
25.338.3753.1

25.338.3853.1
25.338.3953.1
25.338.4053.1

25.338.4153.1
25.338.4253.1
25.338.4353.1

25.338.4453.1
25.338.4553.1
25.338.4653.1

25.338.4753.1
25.338.4853.1
25.338.4953.1

25.338.5053.1
25.338.5153.1
25.338.5253.1

8213 S/..GF part no

marked

25.359.0253.0
25.359.0353.0
25.359.0453.0

25.359.0553.0
25.359.0653.0
25.359.0753.0

25.359.0853.0
25.359.0953.0
25.359.1053.0

25.359.1153.0
25.359.1253.0
25.359.1353.0

25.359.1453.0
25.359.1553.0
25.359.1653.0

25.359.1753.0
25.359.1853.0
25.359.1953.0

25.359.2053.0
25.359.2153.0
25.359.2253.0

5.00mm pin spacing part no

unmarked

25.359.3253.0
25.359.3353.0
25.359.3453.0

25.359.3553.0
25.359.3653.0
25.359.3753.0

25.359.3853.0
25.359.3953.0
25.359.4053.0

25.359.4153.0
25.359.4253.0
25.359.4353.0

25.359.4453.0
25.359.4553.0
25.359.4653.0



25.359.4753.0
25.359.4853.0
25.359.4953.0

25.359.5053.0
25.359.5153.0
25.359.5253.0



Z5.523.2453.0

Z5.523.2453.0


Plug connector



Horizontal socket



Vertical socket



cross section 1 x 1
diameter of drilling hole 1.4mm