



Features


- ◇ For IF GSMSAW filter
- ◇ High attenuation
- ◇ Single-ended operation
- ◇ Dual In-line Package
- ◇ No matching required for operation at 50Ω
- ◇ RoHS compliant (2002/95/EC), Pb-free

Specifications

Parameter	Unit	Minimum	Typical	Maximum
Center Frequency	MHz	89.875	90	90.125
Insertion Loss	dB	-	32.7	38
2dB Bandwidth	MHz	24	24.06	-
3 dB Bandwidth	MHz	-	24.13	-
40 dB Bandwidth	MHz	-	24.84	-
Passband Variation	dB	-	0.9	-
Absolute Delay	usec	-	3.82	4
Ultimate Rejection	$f_0 \pm 12.4\text{MHz}$	dB	25	28
	$f_0 \pm 12.6\text{MHz}$	dB	40	53
	$f_0 \pm 13\text{MHz}$	dB	50	53
	$f_0 \pm 17\text{MHz}$	dB	50	52
Material Temperature coefficient	KHz/°C	-8.46		
Substrate Material	-	YZ LN		
Ambient Temperature	°C	25		
Operating Temperature Range	°C	-40	-	+85
Storage Temperature Range	°C	-45	-	+105
DC Voltage	V	0		
Input Power	dBm	-	-	10
ESD Class	-	1		
Package Size	DIP3512 (35.0x12.8x4.7mm3)			

Notes:

1. All specifications are based on the test circuit shown;
2. In production, all specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature;
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances;
4. This is the optimum impedance in order to achieve the performance show.

	SIPAT Co., Ltd. (CETC No.26 Research Institute) #14 Nanping Huayuan Road, Chongqing, China, 400060	Part Number	LBN09023	
		Rev. Date	2007-10-31	
		Ver.	1.0	Page


Matching Configuration



Source/Load Impedance=50 ohm

Notes - Component values may change depending on board layout.

Package Dimension



Pad Configuration:

Input 1
Output 5
Ground All Others

Marking Configuration:

1) SIPAT: Manufacturer Name
2) LBN09023: Part Number
3) 07XX: Date Code

Package: DIP3512

Unit: mm




SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number	LBN09023	
Rev. Date	2007-10-31	
Ver.	1.0	Page 2/3


Typical Performance

Frequency Respond




Horizontal: 10MHz/Div Vertical: 10dB/Div

Passband Respond




Horizontal: 5MHz/Div Vertical: 0.5dB/Div

Group Delay Variation($f_0 \pm 11.5\text{MHz}$)




Horizontal: 5MHz/Div Vertical: 50ns/Div

Phase Linearity($f_0 \pm 11.5\text{MHz}$)




Horizontal: 5MHz/Div Vertical: 5deg/Div

Smith Chart S11



Smith Chart S22



SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

Part Number	LBN09023	
Rev. Date	2007-10-31	
Ver.	1.0	Page 3/3