

**54ACT11648, 74ACT11648
OCTAL BUS TRANSCEIVERS AND REGISTERS
WITH 3-STATE OUTPUTS**

T-52-31-00

D3458, MARCH 1990-REVISED MAY 1990

- Inputs are TTL-Voltage Compatible
- Independent Registers A and B Buses
- Multiplexed Real-Time and Stored Data
- Inverting Data Paths
- Flow-Through Architecture to Optimize PCB Layout
- Center-Pin V_{CC} and GND Configurations to Minimize High-Speed Switching Noise
- EPIC™ (Enhanced-Performance Implanted CMOS) 1- μ m Process
- 500-mA Typical Latch-Up Immunity at 125°C
- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs

description

These devices consist of bus transceiver circuits with 3-state outputs, D-type flip-flops, and control circuitry arranged for multiplexed transmission of data directly from the data bus or from the internal storage registers. Data on the A or B bus will be clocked into the registers on the low-to-high transition of the appropriate clock pin (CAB or CBA). The following examples demonstrate the four fundamental bus-management functions that can be performed with the octal bus transceivers and registers.

Enable (\bar{G}) and direction (DIR) pins are provided to control the transceiver functions. In the transceiver mode, data present at the high-impedance port may be stored in either register or in both. The select controls (SAB and SBA) can multiplex stored and real-time (transparent mode) data. The circuitry used for select control will eliminate the typical decoding glitch that occurs in a multiplexer during the transition between stored and real-time data. The direction control determines which bus will receive data when enable \bar{G} is active (low). In the isolation mode (control \bar{G} high), A data may be stored in one register and/or B data may be stored in the other register.


When an output function is disabled, the input function is still enabled and may be used to store and transmit data. Only one of the two buses, A or B, may be driven at a time.

The 54ACT11648 is characterized for operation over the full military temperature range of -55°C to 125°C. The 74ACT11648 is characterized for operation from -40°C to 85°C.


EPIC is a trademark of Texas Instruments Incorporated.

UNLESS OTHERWISE NOTED this document contains PRODUCTION DATA information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

54ACT11648 . . . JT PACKAGE
74ACT11648 . . . DW OR NT PACKAGE
(TOP VIEW)



54ACT11648 . . . FK PACKAGE
(TOP VIEW)



Copyright © 1990, Texas Instruments Incorporated



**54ACT11648, 74ACT11648
OCTAL BUS TRANSCEIVERS AND REGISTERS
WITH 3-STATE OUTPUTS**







FIGURE 1. BUS-MANAGEMENT FUNCTIONS

Pin numbers shown are for DW, JT, and NT packages.


54ACT11648, 74ACT11648
OCTAL BUS TRANSCEIVERS AND REGISTERS
WITH 3-STATE OUTPUTS

FUNCTION TABLE


INPUTS						DATA I/O		OPERATION OR FUNCTION
G	DIR	CAB	CBA	SAB	SBA	A1 THRU A8	BI THRU B8	
X	X	↑	X	X	X	Input	Unspecified†	Store A, B unspecified†
X	X	X	↑	X	X	Unspecified†	Input	Store B, A unspecified†
H	X	↑	↑	X	X	Input	Input	Store A and B Data
H	X	H or L	H or L	X	X	Input	Input	Isolation, hold storage
L	L	X	X	X	L	Output	Input	Real-Time \bar{B} Data to A Bus
L	L	X	H or L	X	H	Output	Input	Stored \bar{B} Data to A Bus
L	H	X	X	L	X	Input	Output	Real-Time \bar{A} Data to B Bus
L	H	H or L	X	H	X	Input	Output	Store \bar{A} Data to B Bus

† The data output functions may be enabled or disabled by various signals at the G and DIR inputs. Data input functions are always enabled, i.e., data at the bus pins will be stored on every low-to-high transition on the clock inputs.

logic symbol‡



logic diagram (positive logic)



‡ This symbol is in accordance with ANSI/IEEE Std 91-1984
and IEC Publication 617-12.

Pin numbers shown are for DW, JT, or NT packages.

54ACT11648, 74ACT11648**OCTAL BUS TRANSCEIVERS AND REGISTERS
WITH 3-STATE OUTPUTS****absolute maximum ratings over operating free-air temperature range (unless otherwise noted)[†]**

Supply voltage range, V_{CC}			-0.5 V to 7 V
Input voltage range, V_I (see Note 1)			-0.5 V to $V_{CC} + 0.5$ V
Output voltage range, V_O (see Note 1)			-0.5 V to $V_{CC} + 0.5$ V
Input clamp current, I_{IK} ($V_I < 0$ or $V_I > V_{CC}$)			± 20 mA
Output clamp current, I_{OK} ($V_O < 0$ or $V_O > V_{CC}$)			± 50 mA
Continuous output current, I_O ($V_O = 0$ to V_{CC})			± 50 mA
Continuous current through V_{CC} or GND pins			± 200 mA
Storage temperature range			-65°C to 150°C

[†] Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

recommended operating conditions

		54ACT11648			74ACT11648			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage			0.8			0.8	V
V_I	Input voltage	0		V_{CC}	0		V_{CC}	V
V_O	Output voltage	0		V_{CC}	0		V_{CC}	V
I_{OH}	High-level output current			-24			-24	mA
I_{OL}	Low-level output current			24			24	mA
$\Delta t/\Delta v$	Input transition rise or fall rate	0	10		0	10		ns/V
TA	Operating free-air temperature	-55		125	-40		85	°C

54ACT11648, 74ACT11648
OCTAL BUS TRANSCEIVERS AND REGISTERS
WITH 3-STATE OUTPUTS

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	V _{CC}	T _A = 25°C			54ACT11648		74ACT11648		UNIT
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
V _{OH}	I _{OH} = -50 µA	4.5 V	4.4			4.4		4.4		V
		5.5 V	5.4			5.4		5.4		
	I _{OH} = -24 mA	4.5 V	3.94			3.7		3.8		
		5.5 V	4.94			4.7		4.8		
	I _{OH} = -50 mA†	5.5 V				3.85				
	I _{OH} = -75 mA†	5.5 V						3.85		
V _{OL}	I _{OL} = 50 µA	4.5 V		0.1		0.1		0.1		V
		5.5 V		0.1		0.1		0.1		
	I _{OL} = 24 mA	4.5 V		0.36		0.5		0.44		
		5.5 V		0.36		0.5		0.44		
	I _{OL} = 50 mA†	5.5 V				1.65				
	I _{OL} = 75 mA†	5.5 V						1.65		
I _I	Control Inputs	V _I = V _{CC} or GND	5.5 V		± 0.1		± 1		± 1	µA
I _{OZ}	A or B ports‡	V _I = V _{CC} or GND	5.5 V		± 0.5		± 10		± 5	µA
I _{CC}		V _I = V _{CC} or GND, I _O = 0	5.5 V			8	160		80	µA
ΔI _{CC} §	One input at 3.4 V, Other inputs at GND or V _{CC}	5.5 V		0.9		1		1	1	mA
C _i	Control inputs	V _I = V _{CC} or GND	5 V	4.5						pF
C _{io}	A or B ports	V _I = V _{CC} or GND	5 V	12						

† Not more than one output should be tested at a time, and the duration of the test should not exceed 10 ms.

‡ For I/O ports, the parameter I_{OZ} includes the input leakage current.

§ This is the increase in supply current for each input that is at one of the specified TTL voltage levels rather than 0 V to V_{CC}.

timing requirements, V_{CC} = 5 V ± 0.5 V (see Note 2)

			T _A = 25°C		54ACT11648		74ACT11648		UNIT
			MIN	MAX	MIN	MAX	MIN	MAX	
f _{clock}	Clock frequency		0	75	0	75	0	75	MHz
t _w	Pulse duration, CAB or CBA high or low		6.7		6.7		6.7		ns
t _{su}	Setup time, A before CAB↑ or B before CBA↑		5		5		5		ns
t _h	Hold time, A after CAB↑ or B after CBA↑		2		2		2		ns

NOTE 2: Load circuit and voltage waveforms are shown in Section 1 of the *Advanced CMOS Logic Data Book*, 1990.

54ACT11648, 74ACT11648

**OCTAL BUS TRANSCEIVERS AND REGISTERS
WITH 3-STATE OUTPUTS**

**switching characteristics over recommended operating free-air temperature range,
 $V_{CC} = 5 \text{ V} \pm 0.5 \text{ V}$ (unless otherwise noted) (see Note 2)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	TA = 25°C			54ACT11648		74ACT11648		UNIT
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
f _{max}			75			75		75		MHz
t _{PLH}	A or B	B or A	2.4	6.5	9.5	2.4	11.6	2.4	10.7	ns
			4.4	8.5	11.3	4.4	13.8	4.4	12.7	
t _{PZH}	\bar{G}	A or B	4.2	9.2	13	4.2	15.8	4.2	14.6	ns
			4.3	9.8	13.9	4.3	16.9	4.3	15.6	
t _{PHZ}	\bar{G}	A or B	5.7	8.7	11.3	5.7	12.9	5.7	12.2	ns
			5.3	8.1	10.5	5.3	12.1	5.3	11.4	
t _{PLZ}	CBA or CAB	A or B	5.2	9.4	12	5.2	14.9	5.2	13.7	ns
			6	10.5	13.5	6	16.3	6	15.2	
t _{PLH}	SAB or SBAT (with A or B high)	A or B	4.7	8.6	11.3	4.7	14	4.7	12.9	ns
			3.8	8.6	12	3.8	14.3	3.8	13.4	
t _{PLH}	SBA or SAB† (with A or B low)	A or B	2.6	7.1	10.2	2.6	12.5	2.6	11.5	ns
			5.4	9.7	12.6	5.4	15.2	5.4	14.1	
t _{PZH}	DIR	A or B	3.9	9.8	14.9	3.9	18.4	3.9	16.9	ns
			3.9	10.8	15.1	3.9	18.7	3.9	17.2	
t _{PHZ}	DIR	A or B	4.5	8.2	10.6	4.5	12	4.5	11.5	ns
			3.9	7.3	9.6	3.9	11.9	3.9	11.3	

† These parameters are measured with the internal output state of the storage register opposite to that of the bus input.

NOTE 2: Load circuits and voltage waveforms are shown in Section 1 of the *Advanced CMOS Logic Data Book, 1990*.

operating characteristics, $V_{CC} = 5 \text{ V}$, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS		TYP	UNIT	
	Outputs enabled	$C_L = 50 \text{ pF}$, $f = 1 \text{ MHz}$			
		Outputs disabled			
C _{pd} Power dissipation capacitance per transceivers			61	pF	
			15		