

Part Number: C4008A

Revision: 10/31/2012

1PR 22 AWG (SOLID)TC SRPVC, PVC

COMMUNICATION & CONTROL CABLE

A. CONSTRUCTION

Conductor:	#22 AWG (Solid) Tinned Copper	.025" Nom
Insulation:	.010" Wall, Semi-Rigid Polyvinyl Chloride (SR-PVC)	.044" Nom
Cable Core:	2C @ 6.00" LHL	.088" Nom
Jacket:	.031" Wall, Polyvinyl Chloride (PVC)	.150" Nom
Print Legend:	CAROL (R) 22 AWG -- C4008A -- 75C E105765-H CM (UL) C(UL) OR AWM STYLE 2464 -- CSA LL69381 CMG 60C -- MADE IN USA (DATE CODE) (SEQUENTIAL FOOTAGE)	

DIAMETERS

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464
CSA International	Type CMG

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +75°C
Suggested Working Voltage:	300V Max
Conductor DCR:	17.5 Ohms/1000 ft @ 20°C (max)
Mutual Capacitance:	25.0 pF/ft @ 1kHz (nom)

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED