


7997076 SANYO SEMICONDUCTOR CORP

76C 01983

D

T-52-13-25


STK6942	thick film hybrid IC	CIRCUIT DRAWING No.6044
BIDIRECTIONAL DRIVER FOR DC MOTOR, PULSE MOTOR		 4069

Applications

- VTR
- Printer (Low-voltage type)

Features

- Low-saturation type
- 1-channel type
- Operable from 6V battery


STK6952	thick film hybrid IC	CIRCUIT DRAWING No.6046
2-CHANNEL DC PULSE MOTOR DRIVER		 4068

Use

- Bidirectional drive control of DC motor (VTR, etc.)
- Pulse motor driver

Features

- Low voltage, low saturation
- High current gain
- TTL-level compatible
- Capable of being mounted easily because of small-sized, slim SEP
- Easy thermal design
- 2-channel version of STK6942


STK6962C	thick film hybrid IC	CIRCUIT DRAWING No.6047
DC MOTOR DRIVER		 4052

Use

- DC motor for VTR, CD

Features

- Linear operation, bidirectional drive
- Linear output proportional to input voltage
- Break function available with input open
- Protector against simultaneous input for forward/reverse

STK6965,6966	thick film hybrid IC	CIRCUIT DRAWING No.6048
DC MOTOR DRIVER		 4044

Features

- Linear output proportional to input voltage
 - Brake workable with input open
 - Protection against simultaneous application of forward/reverse drive input
 - Wide operating voltage range
 - Low current dissipation at brake stop mode
- | | | |
|----------------|---------|---------|
| | STK6965 | STK6966 |
| Output current | 4A | 6A |