# BGA Heat Sink (High Aspect Ratio Ext.) **Custom Pin Fin**



ATS Part#:

Description:

**Custom Pin Fin** 

ATS037037002-PF-12A

37.00 x 37.00 x 2.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin

Heat Sink Type: Heat Sink Attachment: Equivalent Part Number: N/A

N/A

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- · High efficiency pin fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance .
- . Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option •

### **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	23.53 °C/W	15.9 °C/W	12.3 °C/W	10.4 °C/W	9.2 °C/W	8.4 °C/W	7.8 °C/W
	Ducted Flow	7	5.9	5.2	4.8	4.4	4.1	3.9

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	тім	Finish
elles	37.00 mm	37.00 mm	2.00 mm	37 mm	N/A	BLACK-ANODIZED
Image above is for illustration purpose only.	<ul> <li>Dimension</li> <li>Dimension</li> <li>Thermal p application</li> <li>ATS resent performant</li> <li>ATS certifier</li> </ul>	n <b>D</b> is fin tip to fin tip performance data are n. rves the right to upda nce.	e provided for refere ate or change its pro	m of the base to the nce only. Actual perf ducts without notice -6 and REACH com ble.	formanc to impr	e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA