



注)
NOTE.

- 各部のそりは0.5最大
WARPING:0.5MAX.
- サーキットNO. はNO. " 1" のみ表示
CIRCUIT NO.: "1" ONLY
- ELV 及び RoHS適合品
ELV AND RoHS COMPLIANT.

10-22-1092	5198-09	45.72	50.72	9
▲ -1082	▲ -08	40.64	45.64	8
-1072	-07	35.56	40.56	7
-1062	-06	30.48	35.48	6
-1052	-05	25.4	30.4	5
-1042	-04	20.32	25.32	4
▼ -1032	▼ -03	15.24	20.24	3
10-22-1022	5198-02	10.16	15.16	2
EDP.NO.	ENG.NO.	B	(A)	極数 CKT.

MATERIAL
NYLON66, 94V-2

REVISED
EC NO: J2008-4096
DRWN:MNABEI
CHKD:THARUYAMA
APPR:NUKITA

DESCRIPTION
GENERAL TOLERANCES (UNLESS SPECIFIED)
10 UNDER ±0.2
10 OVER 30 UNDER ±0.25
30 OVER ±0.3
ANGULAR ±3 °
DRAFT WHERE APPLICABLE
MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE
MM ONLY
DRAWN BY DATE
K. KOHAMA '00/03/28
CHECKED BY DATE
T. YAMAGUCHI '00/03/30
APPROVED BY DATE
M. FUKUSHIMA '00/03/30
MATERIAL NO.
5198-**

SCALE
2:1
DESIGN UNITS
METRIC
THIRD ANGLE PROJECTION
SPOX 10.16/5.08 PITCH
REC HSG
MOLEX INCORPORATED
DOCUMENT NO.
SD-5198-001
SHEET NO.
1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION