# BGA Heat Sink (High Aspect Ratio Ext.) **Straight Fin**





ATS Part#:

Description:

#### ATS015015010-SF-4I

15.00 x 15.00 x 10.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Straight Fin

Heat Sink Type: Straight Fin Heat Sink Attachment: Equivalent Part Number: N/A

superGRIP

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- · High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- Features a low profile, slant fin array that offers many of the performance benefits of maxiFLOW™ at a great value .
- . Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option ٠

### **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	18.1 °C/W	14.3 °C/W	12.3 °C/W	11.1 °C/W	10.1 °C/W	9.4 °C/W	8.8 °C/W
	Ducted Flow	11.4	9.6	8.5	7.7	7.2	6.7	6.3

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	тім	Finish
Mar	15.00 mm	15.00 mm	10.00 mm	15 mm	N/A	BLACK-ANODIZED
Image above is for illustration purpose only.	<ul> <li>Dimension</li> <li>Dimension</li> <li>Thermal papplication</li> <li>ATS resension</li> <li>ATS resension</li> <li>ATS certifier</li> </ul>	n <b>D</b> is fin tip to fin tip performance data are n. rves the right to upd nce.	e provided for refere ate or change its pro k assembly is RoHS	m of the base to the nce only. Actual perf ducts without notice -6 and REACH com ble.	formanc to impr	e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA