

# Data Sheet

## Fujitsu PRIMERGY RX600 S6 Quad socket 4 U rack server

Scalability and balanced composition ensure your growth

The PRIMERGY RX Rack Server family is the perfect platform to form dynamic infrastructures for your business processes today and in the coming decade. You will thus benefit several times over from our recognized experience in optimized data center technology and our innovative strength in developing energy-efficient and cost/performance-optimized rack systems for universal use. PRIMERGY rack servers, built upon industry standards, focus from a functional viewpoint on core features: energy efficiency, reliability, optimized for virtualization, ease of operation and maintenance, flexibility for your future. And thus they notably meet your requirements for outstanding cost efficiency. Optimal operating costs and long-term usability comply with the IT quality required by your customers. Our responsibility goes way beyond the hardware as our tailor-made service packages mean that you can rely on the best support for your IT during its whole lifecycle.

### PRIMERGY RX600 S6

Extensive usage of industry standard x86 based platforms is becoming more important than ever: be it as database management system for medium or large-sized databases or as a consolidation basis to run an immensely large number of different applications using virtualization technologies. The scalable PRIMERGY RX600 S6 is in every respect a reliable server for such critical company scenarios. The ideal interaction of integrated redundancy functions with server management components results in high-level availability and constantly efficient IT production as a character feature of this server platform.

The latest generation of Intel Xeon processors

equipped with up to 10 state-of-the-art cores enable a unique performance boost which however does not bear optimal dividends unless paired with other features: a high extendable main memory capacity with up to 64 DIMMs and a very high number of performant PCI Express channels provide a balanced high throughput architecture so as to meet increasing requirements.

This and the continued evolution of virtualization support via Intel® components (processor, I/O controller) enable a greater consolidation of servers and applications with all the market relevant virtualization solutions, resulting in excellent best-in-class efficiency.



# Features and Benefits

Main Features	Benefits
<p><b>Scale-up Performance for Growth</b></p> <ul style="list-style-type: none"> <li>Using the scalable Intel® QPI architecture in this 4 CPU sockets server results in an excellent increase in performance when compared to the older Front Side Bus server generations. Thanks to the integration of two memory controllers per processor, the CPU to memory bandwidth has been raised up to a factor of 9. Together with the quadrupled maximum memory capacity and the new processor generation with up to 10 cores per processor and 2 threads per core, the system performance achieves unprecedented growth factors.</li> </ul> <p><b>Balanced Scalability</b></p> <ul style="list-style-type: none"> <li>Balanced scale-up performance is achieved by combining various processor choices, using up to 4 x Intel® Xeon® E7-4800 or up to 2 x Intel® Xeon® E7-2800 processors, with PCI Express Generation 2 I/O busses and up to 64 memory DIMMs on 8 configurable memory boards.</li> </ul> <p><b>Integrated High Availability as standard</b></p> <ul style="list-style-type: none"> <li>ECC and SDDC memory protection, memory mirroring support, hot-plug Memory Boards with socket-overlapping memory mirroring, hot-plug redundant fans and power supplies as standard, up to 8x hot-plug 2.5-inch SAS/SATA hard disks, hot-plug PCIe slots</li> <li>LocalView display and integrated Remote Management Controller (iRMC S2) IPMI 2.0 as standard</li> </ul>	<ul style="list-style-type: none"> <li>This system is designed for critical corporate applications and large scale consolidation. Its new architecture ensures for even more efficient deployment of demanding scale-up computing needs. Irrespective of the server usage, as database or virtualization system, the performance can always be extended so that no bottlenecks can arise as a result of low processor performance or main memory capacity.</li> <li>More demanding database loads can be hosted on RX600 S6 with peace of mind, capitalizing on high performance I/O, massive computing power and 1 TB of local memory (up to 2 TB as soon as released) .</li> <li>Large scale consolidation of tier 1 and tier 2 workloads into virtual machines benefit from the high platform reliability and its balanced scalability.</li> <li>More consolidation and virtualization efficiency is obtained by using less server instances with the scale-up RX600 S6 platform. Deployment of “fat VMs” for demanding tier 2 applications can be combined with large scale consolidation of tier 1 virtual machines onto significantly less management instances.</li> <li>Enhanced server reliability without extra cost, operational continuity which means more value for your money as well as secured data safety.</li> <li>Secure management control from wherever your experts are located.</li> </ul>

# Technical details

## PRIMERGY RX600 S6

<b>Housing types</b>	Rack
<b>Mainboard</b>	
<b>Mainboard type</b>	D 3141
<b>Chipset</b>	Intel® 7500 / 7510 Scalable Memory Buffer
<b>Processor quantity and type</b>	2 - 4 x Intel® Xeon® processor E7-2800 series / Intel® Xeon® processor E7-4800 series / Intel® Xeon® processor E7-8800 series
<b>Processor</b>	
	Intel® Xeon® processor E7-2803 (6C/12T, 1.73 GHz, SLC: -, TLC: 18 MB, Turbo: No, 4.8 GT/s, 105 W)
	Intel® Xeon® processor E7-2850 (10C/20T, 2.00 GHz, SLC: -, TLC: 24 MB, Turbo: 1/1/2/3/3, 6.4 GT/s, 130 W)
	Intel® Xeon® processor E7-4807 (6C/12T, 1.86 GHz, SLC: -, TLC: 18 MB, Turbo: No, 4.8 GT/s, 95 W)
	Intel® Xeon® processor E7-4820 (8C/16T, 2.00 GHz, SLC: -, TLC: 18 MB, Turbo: 0/1/1/1/2, 5.86 GT/s, 105 W)
	Intel® Xeon® processor E7-4830 (8C/16T, 2.13 GHz, SLC: -, TLC: 24 MB, Turbo: 0/1/1/1/2, 6.4 GT/s, 105 W)
	Intel® Xeon® processor E7-4850 (10C/20T, 2.00 GHz, SLC: -, TLC: 24 MB, Turbo: 1/1/2/3/3, 6.4 GT/s, 130 W)
	Intel® Xeon® processor E7-4860 (10C/20T, 2.26 GHz, SLC: -, TLC: 24 MB, Turbo: 1/1/2/3/3, 6.4 GT/s, 130 W)
	Intel® Xeon® processor E7-4870 (10C/20T, 2.40 GHz, SLC: -, TLC: 30 MB, Turbo: 1/1/2/3/3, 6.4 GT/s, 130 W)
	Intel® Xeon® processor E7-8837 (8C/8T, 2.67 GHz, SLC: -, TLC: 24 MB, Turbo: 0/1/1/1/1, 6.4 GT/s, 130 W)
<b>Processor notes</b>	A minimum of 2 processors must be configured, no mix of different processor types E7-2800 CPU 's can be configured max. 2x
<b>Memory slots</b>	64 (distributed on 8 memory boards with 8 slots each)
<b>Memory slot type</b>	DIMM (DDR3) LV
<b>Memory capacity (min. - max.)</b>	8 GB - 2048 GB
<b>Memory protection</b>	Advanced ECC SDDC Memory Scrubbing Memory DIMM Sparing support Memory Mirroring support
<b>Memory notes</b>	Memory modules are installed on memory boards (8 DIMM slots per memory board) Two memory boards are preinstalled in base unit, further memory boards as option
<b>Memory options</b>	
	16 GB (4 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	32 GB (4 module(s) 8 GB) DDR3 LV, registered, ECC, 1066 MHz, PC3-8500, DIMM
	32 GB (4 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	64 GB (4 module(s) 16 GB) DDR3 LV, registered, ECC, 1066 MHz, PC3-8500, DIMM
<b>Memory modules notes</b>	Memory modules will be delivered in set's of 4 DIMMs per order code. Intel® 7510 Scalable Memory Buffer supports max. 1066MHz memory clock speed. Clock speed is also depending on the processor type.  2TB memory capacity will be possible when 32GB DIMM modules are available.
<b>Interfaces</b>	
<b>USB ports</b>	6 x USB 2.0 (3 x front, 2 x rear, 1 x internal)
<b>Graphics (15-pin)</b>	2 x VGA (1 x front, 1 x rear)
<b>Serial 1 (9-pin)</b>	1 x RS-232-C

**Interfaces**

LAN / Ethernet	4 x Gbit/s Ethernet (RJ45)
Service LAN (RJ45)	1 x dedicated service LAN port for iRMC S2 (10/100 Mbit/s) Service LAN traffic can be switched to shared onboard Gbit LAN port

**Onboard or integrated Controller**

RAID controller	8 Port SAS RAID 0/1 or RAID 5/6 controller as option See under Components RAID controller
LAN Controller	2 x Intel® 82576, 4 x 10/100/1000 Mbit/s Ethernet, TCP/IP acceleration, PXE boot via LAN from PXE server
Remote Management Controller	Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / separate module; TCG V1.2 compliant (option)

**Slots**

PCI-Express 2.0 x4 (mech. x8)	3 x Full height (2 x ½ length, 1 x ¾ length)
PCI-Express 2.0 x8	4 x Full height (all ¾ length, 2x hot-plug)
PCI-Express 2.0 x16	1 x Full height (all ¾ length)
PCI-Express x4 (mech. x8)	2 x Half height (all ½ length)
Storage drive bays	8 x 2.5-inch hot-plug
Accessible drive bays	1 x 5.25/0.5-inch for CD-RW/DVD 1 x 5.25/1.6-inch for backup devices

**General system information**

Number of fans	8
Fan configuration	hot-plug

**Operating panel**

Operating buttons	On/off switch NMI button Reset button ID button
Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (orange / yellow) Identification (blue)
Service display	ServerView Local Service Display (LSD)

**BIOS**

BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support
---------------	--

**Operating Systems and Virtualization Software**

<b>Certified or supported operating systems and virtualization software</b>	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows® Server 2008 Datacenter
	Microsoft® Windows® Server 2008 Enterprise
	Microsoft® Windows® Server 2008 Standard
	VMware vSphere™ 5.0 Embedded
	VMware vSphere™ 5.0
	VMware vSphere™ 4.1
	VMware vSphere™ 4.1 Embedded
	VMware vSphere™ 4.1 Installable
	Novell® SUSE Linux Enterprise Server 11
	Novell® SUSE Linux Enterprise Server 10
	Novell® SUSE Linux Enterprise Server 10 with XEN
	Red Hat® Enterprise Linux 6
	Red Hat® Enterprise Linux 5
Red Hat® Enterprise Linux 5 with XEN	
Citrix® XenServer®	
<b>Operating system release link</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=a9e600b9-e4cb-4f48-aa41-632f69058421">http://docs.ts.fujitsu.com/dl.aspx?id=a9e600b9-e4cb-4f48-aa41-632f69058421</a>
<b>Operating system notes</b>	Support of other Linux derivatives on demand

**Server Management**

<b>Standard</b>	<ul style="list-style-type: none"> <li>ServerView Suite - Deploy <ul style="list-style-type: none"> <li>SV Installation Manager</li> <li>SV Scripting Toolkit</li> <li>SV Deployment Manager (30-day trial version)</li> </ul> </li> <li>ServerView Suite - Control <ul style="list-style-type: none"> <li>SV Operations Manager incl. PDA and ASR &amp; R (Prefailure and Analysis; Automatic Server Recovery and Restart)</li> <li>SV Performance Management</li> <li>SV Power Management</li> <li>SV RAID Manager</li> </ul> </li> <li>ServerView Suite - Maintain <ul style="list-style-type: none"> <li>SV Remote Management (iRMC)</li> <li>SV Update Management (BIOS, Firmware, Windows Drives and SV Agents)</li> <li>SV Asset Management</li> <li>SV Online Diagnostics</li> </ul> </li> <li>ServerView Suite - Integrate <ul style="list-style-type: none"> <li>SV Integration packs e.g. for Microsoft System Center, Nagios, HP, SIM, HP NNM, IBM Tivoli, Altiris</li> </ul> </li> </ul> Deployment Solutions and others
<b>Option</b>	<ul style="list-style-type: none"> <li>ServerView Suite - Deploy <ul style="list-style-type: none"> <li>SV Deployment Manager (full version)</li> </ul> </li> <li>ServerView Suite - Maintain <ul style="list-style-type: none"> <li>iRMC Advanced Pack incl. Advanced Video Redirection (AVR) and Remote Storage</li> </ul> </li> <li>ServerView Suite - Dynamize <ul style="list-style-type: none"> <li>SV Virtual-IO Manager (VIOM)</li> <li>SV Resource Orchestrator Virtual Edition (ROR VE)</li> <li>SV Resource Orchestrator Cloud Edition (ROR CE)</li> </ul> </li> <li>ServerView Suite - Integrate <ul style="list-style-type: none"> <li>SV Integration pack for Fujitsu ManageNow® solution</li> </ul> </li> </ul>
<b>Server Management notes</b>	Regarding Operating System dependencies and product details for ServerView Suite Software Products see dedicated Product Data sheets.

**Dimensions / Weight**

<b>Rack (W x D x H)</b>	482.6 mm (Bezel) / 445mm (Body) x 765 x 176 mm
<b>Mounting Depth Rack</b>	728 mm

<b>Dimensions / Weight</b>	
Height Unit Rack	4 U
19" rackmount	Yes
Mounting Cable depth rack	100 mm (1000 mm Rack recommended)
Weight	max. 46 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option
<b>Environmental</b>	
Operating ambient temperature	10 - 35°C
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation locations)
Operating environment Link	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473">http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473</a>
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	50 dB(A) (idle) / 50 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	6.5 B (idle) / 6.6 B (operating)
Noise notes / description	at ambient temperature <23°C
<b>Electrical values</b>	
Power supply configuration	Up to 4 hot plug power supplies. Base unit equipped with 2 power supplies, 3rd and 4th PSU as option
Max. output of single power supply	850 W
Power supply efficiency	92% (at 50% PSU load, CSCI "gold")
Hot-plug power supply redundancy	Yes
Rated voltage range	100 V - 127 V / 200 V - 240 V
Rated frequency range	47 Hz - 63 Hz
Rated current max.	26 A / 11 A (100 V / 240 V)
Active power (min. configuration)	750 W
Active power (max. configuration)	1790 W
Rated power max.	2640 W
Heat emission	6444.0 kJ/h (6107.7 BTU/h)
<b>Compliance</b>	
Germany	GS
Europe	CE Class A *
USA/Canada	CSAc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
Japan	VCCI
Taiwan	BSMI
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	<a href="http://sp.ts.fujitsu.com/sites/certificates/">http://sp.ts.fujitsu.com/sites/certificates/</a>

# Components

<b>Storage disks</b>	SSD SAS, 6 Gb/s, 400 GB, SLC, hot-plug, 2.5-inch, enterprise
	SSD SAS, 6 Gb/s, 200 GB, SLC, hot-plug, 2.5-inch, enterprise
	SSD SAS, 6 Gb/s, 100 GB, SLC, hot-plug, 2.5-inch, enterprise
	PCIe SSD, 640 GB, MLC, Flash drive
	PCIe SSD, 320 GB, MLC, Flash drive
	HDD SAS, 6 Gb/s, 900 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 600 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 450 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 146 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 73 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise	
<b>Backup Drives</b>	DDS Gen5, 36 GB, 3 MB/s, half height, USB 2.0
	DDS Gen6, 80 GB, 6 MB/s, half height, USB 2.0
	LTO3HH Ultrium, 400 GB, 60 MB/s, half height, SAS 3Gb/s
	LTO4HH Ultrium, 800 GB, 120 MB/s, half height, SAS 6Gb/s
	LTO5HH Ultrium, 1500 GB, 140 MB/s, half height, SAS 6Gb/s
	RDX Drive, 160 GB, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 2.0
<b>Optical drives</b>	Blu-ray Disc™ Triple Writer, (6x BD-ROM; 8x DVD; 24x CD), slimline, SATA I
	DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I
<b>SCSI / SAS Controller</b>	SCSI Ctrl. 320 MB 1ch int/ext PCIe x1
	SAS Ctrl. 6 Gb 8 ports ext. PCIe Gen2 x8
	SAS Ctrl. 3 Gb 4 ports int. / 4 ports ext. PCIe x4
<b>RAID Controller</b>	Integrated RAID 5/6 Ctrl., HDD SAS 6 Gb, Fujitsu , 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)
	Integrated RAID 0/1 Ctrl., SAS/SATA 6 Gb, Fujitsu , 8 ports int. RAID level: 0, 1, 10, No BBU support (based on LSI SAS2008)
	Integrated RAID 0/1 Ctrl., SAS/SATA 3 Gb, 4 ports int. RAID level: 0, 1, 1E, No BBU support (based on LSI 1064e)
<b>Fibre Channel controller</b>	Fibre Channel Host Bus Adapter 1 x 8 Gb Qlogic QLE2560 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gb Qlogic QLE2562 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 8 Gb Emulex LPe1250 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gb Emulex LPe12002 MMF LC-style
<b>LAN Controller</b>	Converged Network Adapter 2 x 10 Gb Emulex OCe10102
	Ethernet Ctrl. 1 x 1 Gb Intel® PRO/1000 PF Server Adapter
	Ethernet Ctrl. 2 x 10 Gb Fujitsu Eth Ctrl 2x10Gbit PCIe x8 D2755 SFP+
	Ethernet Ctrl. 2 x 1 Gb Fujitsu LAN Adapter D2735-2
	Ethernet Ctrl. 4 x 1 Gb Fujitsu Eth Ctrl 4x1Gbit PCIe x4 D2745 Cu
	InfiniBand HCA 1 x 40 Gb Mellanox InfiniBand HCA 2 x 40 Gb Mellanox
<b>Rack infrastructure</b>	Cable Arm 2U for PCR M1 S and 3rd party racks
	Rackmount kit full extraction (760mm), tool less mounting with quick release lever
	Cable Management for asym. 19-inch PRIMECENTER Racks
<b>Warranty</b>	
<b>Standard Warranty</b>	3 years
<b>Service level</b>	On-site Service (depending on country)

---

**Warranty**

**Maintenance and Support Services - the perfect extension**

---

**Recommended Service** 7x24, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.

---

**Service Lifecycle** 5 years

---

**Service Weblink** <http://www.fujitsu.com/fts/services>



# More information

## Fujitsu platform solutions

In addition to Fujitsu PRIMERGY RX600 S6, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

### Computing Products

[www.fujitsu.com/global/services/computing/](http://www.fujitsu.com/global/services/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about Fujitsu PRIMERGY RX600 S6, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/fts](http://www.fujitsu.com/fts)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright © Fujitsu Technology Solutions

## Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

## CONTACT

FUJITSU LIMITED  
Mies-van-der-Rohe-Straße 8  
80807 München  
Germany  
Website: [www.ts.fujitsu.com](http://www.ts.fujitsu.com)  
2012-04-04 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright © Fujitsu Technology Solutions