

<p><b>0291</b></p> <p><b>0291-0-15-XX-16-XX-10-0</b> Hex press-fit in .067 plated thru hole</p>	<p><b>0293</b></p> <p><b>0293-0-15-XX-16-XX-10-0</b> Press-fit in .067 mounting hole</p>	<p><b>0287</b></p> <p><b>0287-0-15-XX-16-XX-10-0</b> Solder mount in .065 min. mounting hole Also available on 8mm wide carrier tape: 3,250 parts per 13" reel. Order as: 0287-0-57-XX-16-XX-10-0</p>	<p><b>0285</b></p> <p><b>0285-0-15-XX-16-XX-10-0</b> Solder mount in .065 min. mounting hole</p>
---	--	---	--

<p><b>0284</b></p> <p><b>0284-0-15-XX-16-XX-10-0</b> Solder mount in .070 min. mounting hole</p>	<p><b>8114</b></p> <p><b>8114-0-15-XX-16-XX-04-0</b> Press-fit from underside of pc board into .065 mounting hole</p>	<p><b>0407</b></p> <p><b>0407-0-15-XX-16-XX-04-0</b> Press-fit in .066 mounting hole</p>	<p><b>0415</b></p> <p><b>0415-0-15-XX-16-XX-10-0</b> Solder mount in .063 min. mounting hole Also available on 24mm wide carrier tape: 1,500 parts per 13" reel. Order as: 0415-0-57-XX-16-XX-10-0</p>
--	---	--	--

<p><b>0303</b></p> <p><b>0303-0-19-XX-16-XX-10-0</b> Wire Termination Press-fit in .067 mounting hole</p>	<p><b>0306</b></p> <p><b>0306-0-19-XX-16-XX-10-0</b> Wire Termination #18 gage crimp barrel</p>	<p><b>0273</b></p> <p><b>0273-0-15-XX-16-XX-10-0</b> Press-fit in .078 mounting hole</p>	<p><b>7520</b></p> <p><b>7520-0-15-XX-16-XX-10-0</b> Press-fit in .066 mounting hole</p>
---	---	--	--

<p><b>SPECIFICATIONS</b></p> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES</b> <b>TOLERANCES ON:</b> LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - 1X - XX - 16 - XX - XX - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b></p> <ul style="list-style-type: none"> <li>01 200μ" TIN/LEAD OVER NICKEL</li> <li>◇ 80 200μ" TIN OVER NICKEL (RoHS)</li> <li>◇ 15 10μ" GOLD OVER NICKEL (RoHS)</li> </ul> <p><b>SPECIFY CONTACT FINISH:</b></p> <ul style="list-style-type: none"> <li>01 200μ" TIN/LEAD OVER NICKEL</li> <li>◇ 80 200μ" TIN OVER NICKEL (RoHS)</li> <li>◇ 27 30μ" GOLD OVER NICKEL (RoHS)</li> </ul> <p align="center"><b>CONTACT</b></p> <p align="center">#16 CONTACT (DATA ON PAGE 221)</p>
--	--