

## GMSM Low Profile Single Row Metal Shell Microminiature Solder Cup and Pre-Wired Connectors



**GMSM Connectors** offer mil spec design and performance in a smaller form factor. These GMSM single row connectors are reduced in height compared to two-row Micro-D connectors.

**GMSM Connectors** feature gold plated TwistPin contacts, machined aluminum shells, and are fully potted with epoxy. Choose from 4 to 35 contacts. Available in a variety of finishes, socket connectors are fitted with flourosilicone interfacial seals.

HOW TO ORDER GMSM SOLDER CUP CONNECTORS									
	Series	Shell Finish	Number of Contacts	Contact Type	Termination Type	Hardware			
Solder Cup	GMSM	<ol> <li>Cadmium</li> <li>Nickel</li> <li>Black Anodize</li> <li>Gold</li> <li>Chem Film</li> </ol>	4 6 10 15 20 25 30 35	P - Pin S - Socket	S Solder Cup	B M M1 S S1 L K F			
	Sample Part Number								
	GMSM	1 –	15	Р	S	В			

	MICRO-D MOUNTING HARDWARE													
	В	Р	M	M1	S	S1	L	K	F	R				
(		00			73									
	Thru-Hole Order Hardware Separately	Jackpost Removable Includes Nut and Washer	Jackscrew Hex Head Removable E-ring	Jackscrew Hex Head Removable E-ring Extended	Jackscrew Slot Head Removable E-ring	Jackscrew Slot Head Removable E-ring Extended	Jackscrew Hex Head Non- Removable	Jackscrew Slot Head Non- Removable Extended	Float Mount For Front Panel Mounting	Float Mount For Rear Panel Mounting				

© 2006 Glenair, Inc. CAGE Code 06324/0CA77 Printed in U.S.A.