

1		2		3		4		5		6		7		8	
REVISIONS															
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE													
<p>NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)</p> <p>1. BRASS PER QQ-B-626</p> <p>2. BERYLLIUM COPPER PER QQ-C-530</p> <p>3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>5. TEFLON MIL-P-19468</p> <p>6. JIS H 3250, C 2700</p>															
<p>1. CRIMPED FERRULE HEX CRIMP SIZE .178"</p> <p>2. CONTACT PIN TO SOLDER</p>															
7	FERRULE	NOTE 6	NOTE 3	1	FR-51/4x127	DIMENSIONS ARE IN MILLIMETERS		PART NO.		<p>Amphenol</p> <p>TITLE 1.0/2.3 CRIMP PLUG</p> <p>DRAWING NO.</p> <p>ITEM NO.</p>					
6	CONTACT PIN	NOTE 1	NOTE 4	1	1231121D2-6-08/06	UNLESS OTHERWISE SPECIFIED TOLERANCES		1231121D3-N/3GT3G-ST212-75							
5	OUT CONTACT	NOTE 2	NOTE 4	1	1231121D1-6-B	0.5-6 = ±0.2		APPROVED DATE							
4	INSULATOR	NOTE 5	NATURAL	1	1231121D2-4T-75	6-30 = ±0.4		DATE 10-11-01'							
3	SPRING	NOTE 2	NATURAL	1	123-PLUG-SPR	30-120 = ±0.6		CHECKED DATE							
2	BODY	NOTE 1	NOTE 3	1	1231121D3-2-336/22	120-315 = ±1		DATE 10-11-01'							
1	SHELL	NOTE 1	NOTE 3	1	1231121D2-1	315-1000 = ±1.6		DRAWN DATE							
NO.		DESCRIPTION		MATERIAL		FINISH		Q'TY		DRAWING NO.		SCALE		4/1 ISSUE A	
														FILE NO.	

1 2 3 4 5 6 7 8