




FS/FD™ 10-30A Metallic

Metallic Plugs, Connectors, Receptacles and Reverse Service Female Plugs/Male Inlets.

10-30A, Maximum 600 VAC/250VDC

Female Receptacles		Reverse Service			
		Female Plugs		Male Receptacles	
					
				(Inlets)	
Aluminum with Box **	Cast Brass with Box **	Aluminum	Cast Brass	Aluminum w/Box FDWS-62	Cast Brass w/Box 3731
3743U-2	3763U-2	3789U-2	3789BU-2	3776U-2	3779U-2
3743U-3	3763U-3	3789U-3	3789BU-3	3776U-3	3779U-3
3743U-4	3763U-4	3789U-4	3789BU-4	3776U-4	3779U-4
3743U-5	3763U-5	3789U-5	3789BU-5	3776U-5	3779U-5
3743	3763	3789	3789B	3776	3779
3743U-1	3763U-1	3789U-1	3789BU-1	3776U-1	3779U-1
3753	3773	3809 ¹	3809B ¹	3796 ²	3799 ³
3744	3764	3790	3790B	3777	3780
3744	3764	3790	3790B	3777	3780
3754	3774	3810	3810B	3797	3800
3754	3774	3810	3810B	3797	3800

** Receptacles come with the following boxes:

Material	Amperes	Box
Aluminum	10, 15 & 20 30	FSWS-62 FDWS-62
Brass	10, 15 & 20 30	3721 3731

1 Also in plastic. Use 3809P or 9F33U0

2 Also in plastic. Use 3796PA – Aluminum back box (use 3797-P for brass)

3 Also in plastic. Use 3799P (Brass J-Box) or 9B33U0F (w/o J-Box)

Notes:

- For 20/30A thermoplastic devices, see DuraGard section.
- Mating with DuraGard Line
 - 20A devices will mate and lock across lines.
 - 30A metal male devices cannot mate to DuraGard 30A female devices can be mixed.

For NEMA style (bladed) Convenience Receptacles, see page 62.