

## ST 18/3 poles Male parts


single screw connector strain relief for one round cable diameter 6.5-8.3 mm

single screw connector strain relief for two round cables diameter 4.5-10.0 mm or one flat cable

double screw connector strain relief for one round cable diameter 6.5-8.3 mm









maie p	oarτ	asser	mblea		
with st	rain	relief	without	locking	device
black			93.734.3	353.0	100
white			93.734.3	350.0	100
areen/hla	00k11		93 734 3	750 0	100



male part a	assembled
with strain r	relief without locking device
black	<b>93.634.3353.0</b> 100
white	<b>93.634.3350.0</b> 100
green/black <sup>1:</sup>	<b>93.634.3750.0</b> 100



male part assembled with strain relief without locking device black 93.734.6353.0 93.734.6350.0 white 200

green/black <sup>11</sup>	93.734.3750.0	100	
male part as with strain re	sembled lief with locking de	vice	
black white green/black <sup>1)</sup>	93.734.4353.0 93.734.4350.0 93.734.4750.0	100 100 100	
male part unassembled			

male part assembled			
with strain relief with locking device			
black	93.634.4353.0	100	
white	93.634.4350.0	100	
green/black11	93.634.4750.0	100	

male part assembled		
with strain relief	with locking dev	rice
black	93.734.7353.0	200
white	93.734.7350.0	200

male part unassembled			
with strain relief	without locking	device	
black	93.934.3353.0	200	
white	93.934.3350.0	200	
green/black1)	93.934.3750.0	200	

male part	unassembled	
with strain	relief without locking device	
black	93.834.3353.0 200	
white	93.834.3350.0 200	
green/black1)	<b>93.834.3750.0</b> 200	

white	93.734.7350.0	200
male part u	nassembled	

male part unassembled			
with strain relief with locking device			
black	93.934.4353.0	200	
white	93.934.4350.0	200	
green/black <sup>1)</sup> <b>93.934.4750.0</b> 200			
1) female part green, strain relief black			

male part unas with strain relief	sembled with locking de	vice
black	93.834.4353.0	200
white	93.834.4350.0	200
green/black <sup>11</sup>	93.834.4750.0	200

าก	
	00

with strain relief without locking device



green/black <sup>11</sup>	93.834.4750.
female part green, (attention: watch of	

with strain relief with locking device 93.934.7353.0 93.934.7350.0 200





.,	female part green, strain relief	blac
	(attention: watch coding!)	
	_	





200

ma	le.	Dа	rτ

black	93.032.3353.0	200
white	93.032.3350.0	200
green	93.032.3750.0	200

male	part
black	

naic part			
lack	93.032.3353.0	200	
vhite	93.032.3350.0	200	
reen	93.032.3750.0	200	

strain relief complete with top and bottom part

male part

white

•		
olack	93.032.6353.0	200
white	93.032.6350.0	200

strain relief complete with top and bottom part | strain relief complete with top and bottom part wi

without locking	g device		without locking	device	
black	Z7.419.2553.0	200	black	Z7.419.5253.0	200
white	Z7.419.2553.2	200	white	Z7.419.5253.2	200

strain relief complete with top and bottom pa without locking device black Z7.419.2453.0 200

Z7.419.2453.2

strain relief complete with top and bottom part
with locking device

WITH IOCKII	ig device	
black	Z7.419.5053.0	200
white	Z7.419.5053.2	200

strain relief complete with top and bottom p

black	Z7.419.2053.0	200
white	Z7.419.2053.2	200

with locking device black Z7.419.2353.0 200 white Z7.419.2353.2 200