



P-Channel 20-V (D-S) MOSFET

These miniature surface mount MOSFETs utilize High Cell Density process. Low $r_{DS(on)}$ assures minimal power loss and conserves energy, making this device ideal for use in power management circuitry. Typical applications are DC-DC converters, power management in portable and battery-powered products such as computers, printers, PCMCIA cards, cellular and cordless telephones.

- Low $r_{DS(on)}$ Provides Higher Efficiency and Extends Battery Life
- Miniature SOT-23 Surface Mount Package Saves Board Space
- Fast switching speed
- High performance trench technology

| PRODUCT SUMMARY | | |
|-----------------|--------------------------|-----------|
| V_{DS} (V) | $r_{DS(on)}$ (OHM) | I_D (A) |
| -20 | 0.052 @ $V_{GS} = -4.5V$ | -3.6 |
| | 0.072 @ $V_{GS} = -2.5V$ | -3.1 |
| | 0.120 @ $V_{GS} = -1.8V$ | -2.7 |



| ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ C$ UNLESS OTHERWISE NOTED) | | | | |
|---|------------------|----------------|------------|------------|
| Parameter | | Symbol | Ratings | Units |
| Drain-Source Voltage | | V_{DS} | -20 | V |
| Gate-Source Voltage | | V_{GS} | ± 8 | |
| Continuous Drain Current ^a | $T_A=25^\circ C$ | I_D | -3.6 | A |
| | $T_A=70^\circ C$ | | -1.8 | |
| Pulsed Drain Current ^b | | I_{DM} | -10 | |
| Continuous Source Current (Diode Conduction) ^a | | I_S | ± 0.46 | A |
| Power Dissipation ^a | $T_A=25^\circ C$ | P_D | 1.25 | W |
| | $T_A=70^\circ C$ | | 0.8 | |
| Operating Junction and Storage Temperature Range | | T_J, T_{stg} | -55 to 150 | $^\circ C$ |

| THERMAL RESISTANCE RATINGS | | | | |
|--|----------------|------------|---------|--------------|
| Parameter | | Symbol | Maximum | Units |
| Maximum Junction-to-Ambient ^a | $t \leq 5$ sec | R_{THJA} | 100 | $^\circ C/W$ |
| | Steady-State | | 150 | |

Notes

- a. Surface Mounted on 1" x 1" FR4 Board.
- b. Pulse width limited by maximum junction temperature

| SPECIFICATIONS (T _A = 25°C UNLESS OTHERWISE NOTED) | | | | | | |
|---|---------------------|--|--------|-------|------|------|
| Parameter | Symbol | Test Conditions | Limits | | | Unit |
| | | | Min | Typ | Max | |
| Static | | | | | | |
| Gate-Threshold Voltage | V _{GS(th)} | V _{DS} = V _{GS} , I _D = -250 uA | -0.7 | | | |
| Gate-Body Leakage | I _{GSS} | V _{DS} = 0 V, V _{GS} = ±8 V | | | ±100 | nA |
| Zero Gate Voltage Drain Current | I _{DSS} | V _{DS} = -16 V, V _{GS} = 0 V | | | -1 | uA |
| | | V _{DS} = -16 V, V _{GS} = 0 V, T _J = 55°C | | | -10 | |
| On-State Drain Current ^A | I _{D(on)} | V _{DS} = -5 V, V _{GS} = -4.5 V | -10 | | | A |
| Drain-Source On-Resistance ^A | r _{DS(on)} | V _{GS} = -4.5 V, I _D = -3.6 A | | | 52 | mΩ |
| | | V _{GS} = -2.5 V, I _D = -3.1 A | | | 72 | |
| | | V _{GS} = -1.8 V, I _D = -2.7 A | | | 120 | |
| Forward Transconductance ^A | g | V _{GS} = -5 V, I _D = -1.25 A | | 12 | | S |
| Diode Forward Voltage | V _{SD} | I _S = -0.46 A, V _{GS} = 0 V | | -0.60 | | V |
| Dynamic^b | | | | | | |
| Total Gate Charge | Q _g | V _{DS} = -5 V, V _{GS} = -4.5 V, I _D = -2.4 A | | 12.0 | | nC |
| Gate-Source Charge | Q _{gs} | | | 2.0 | | |
| Gate-Drain Charge | Q _{gd} | | | 2.0 | | |
| Input Capacitance | C _{iss} | P-Channel V _{DS} = -15V, V _{GS} = 0V, f = 1MHz | | 1312 | | pF |
| Output Capacitance | C _{oss} | | | 130 | | |
| Reverse Transfer Capacitance | C _{rss} | | | 106 | | |
| Turn-On Delay Time | t _{d(on)} | V _{DD} = -10 V, I _L = -1 A, V _{GEN} = -4.5 V, R _G = 6 Ω | | 6.5 | | ns |
| Rise Time | t _r | | | 20 | | |
| Turn-Off Delay Time | t _{d(off)} | | | 31 | | |
| Fall-Time | t _f | | | 21 | | |

Notes

- Pulse test: PW ≤ 300us duty cycle ≤ 2%.
- Guaranteed by design, not subject to production testing.

FREESCALE reserves the right to make changes without further notice to any products herein. FREESCALE makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does FREESCALE assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in FREESCALE data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typical" must be validated for each customer application by customer's technical experts. FREESCALE does not convey any license under its patent rights nor the rights of others. FREESCALE products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the FREESCALE product could create a situation where personal injury or death may occur. Should Buyer purchase or use FREESCALE products for any such unintended or unauthorized application, Buyer shall indemnify and hold FREESCALE and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that FREESCALE was negligent regarding the design or manufacture of the part. FREESCALE is an Equal Opportunity/Affirmative Action Employer.

Typical Electrical Characteristics




Figure 1. On-Region Characteristics




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage




Figure 3. On-Resistance Variation with Temperature




Figure 4. On-Resistance Variation with Gate to Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature

Typical Electrical Characteristics




Figure 7. Gate Charge Characteristic




Figure 8. Capacitance Characteristic




Figure 9. Maximum Safe Operating Area




Figure 10. Single Pulse Maximum Power Dissipation

Normalized Thermal Transient Junction to Ambient






Figure 11. Transient Thermal Response Curve.

Package Information



| DIM. | MILLIMETERS | | |
|------|-------------|------|-------|
| | MIN | NOM | MAX |
| A | 0.935 | 0.95 | 1.10 |
| A1 | 0.01 | --- | 0.10 |
| A2 | 0.85 | 0.90 | 0.925 |
| b | 0.30 | 0.40 | 0.50 |
| c | 0.10 | 0.15 | 0.25 |
| D | 2.70 | 2.90 | 3.10 |
| E | 2.60 | 2.80 | 3.00 |
| E1 | 1.40 | 1.60 | 1.80 |
| e | 0.95 BSC | | |
| e1 | 1.90 BSC | | |
| L | 0.30 | 0.40 | 0.60 |
| L1 | 0.60REF | | |
| L2 | 0.25BSC | | |
| R | 0.10 | --- | --- |
| θ | 0° | 4° | 8° |
| θ1 | 7°NOM | | |



Ordering information

- AM2327P-T1-XX
 - A: Analog Power
 - M: MOSFET
 - 2327: Part number
 - P: P-Channel
 - T1: Tape & reel
 - XX: Blank: Standard
PF: Leadfree