




order number: L00006A0037

Patch Cord Cat.7 MP8 FS 600 LSZH-15,0 m, green



Schaltbild / Connection Diagram



Technical Attributes	
Short name	MP8 FS 600 LSZH-15,0
Length	15,0 m
Colour	green

Performance Characteristics

- termination sequence acc. to EIA/TIA 568
- 360 degrees completely surround plug shielding (shielded cable types)
- flexible and strain relieved
- moulded strain relief boot
- cable jacket and strain relief boot: PVC resp. LSZH (= Low Smoke, Zero Halogen)

Mechanical Characteristics	
Cable structure	Li02YSCH 4x2xAWG 27/7 PiMF
Stranded wire	AWG 27 (7/0.14 mm)
Insulation	PE, Ø 1.04 mm (±0.05 mm)

Pair shielding	Al-foil, outside conducting
Overall shielding	tin plated copper braid
Outer jacket	5.7 mm (±0.2 mm)

Climatic Characteristics	
flame-retardant test	IEC 60332-1
UL approval	
Operating temperature	-20°C ... 60°C

Electrical Characteristics	
Current carrying capacity at 50°C	1 A
PoE+ acc to IEEE 802.3at	Adequate for Power over Ethernet+

Standards	
Connectors	IEC 60603-7-5

Transmission Characteristics	
10 Gigabit Ethernet acc. to IEEE 802.3an	Adequate for 10 Gigabit Ethernet
Gigabit Ethernet acc. to IEEE 802.3	