


PANDUIT® PAN-TERM® Ring Terminals

RING TERMINALS LARGE WIRE


Vinyl Expanded Insulation

- For Large Wire Insulation O.D.
- Insulation Support
- Brazed Seam



Non-Insulated


- Brazed Seam
- Beveled Wire Lead-In



HEAVY DUTY - LARGE WIRE

Non-Insulated

- Brazed Seam
- Extra Thick Tongue for High Strength Applications
- Tin Plated Copper
- UL Listed and CSA Certified for 302°F (150° C) Maximum Operating Temperature



Part Number	Wire Range	Color Code	Max. Ins.	Stud Size	Dimensions (In.)				Std. Ctn. Qty.	Std. Ctn. Qty.	Bulk Pkg. Qty.	Bulk Ctn. Qty.
					A	W	C	G				
PV8-8RX-Q	8 .040 Stock	Red	.360	#8	1.50	.42	.43	1.29	25	250	200	1200
PV8-10RX-Q		Red	.360	#10	1.52	.47	.43	1.29	25	250	200	1200
PV8-14RX-Q		Red	.360	1/4"	1.52	.47	.43	1.29	25	250	200	1200
PV8-56RX-Q		Red	.360	5/16"	1.62	.59	.51	1.33	25	250	200	1200
PV8-38RX-Q		Red	.360	3/8"	1.62	.59	.51	1.33	25	250	200	1200
PV8-12RX-Q	Red	.360	1/2"	1.74	.82	.51	1.33	25	250	200	1200	
PV6-8RX-E	6 .045 Stock	Blue	.436	#8	1.61	.47	.43	1.37	20	200	200	1200
PV6-10RX-E		Blue	.436	#10	1.61	.47	.43	1.37	20	200	200	1200
PV6-14RX-E		Blue	.436	1/4"	1.61	.47	.43	1.37	20	200	200	1200
PV6-56RX-E		Blue	.436	5/16"	1.73	.62	.51	1.42	20	200	200	1200
PV6-38RX-E		Blue	.436	3/8"	1.73	.62	.53	1.42	20	200	200	1200
PV6-12RX-E	Blue	.436	1/2"	1.83	.82	.53	1.42	20	200	200	1200	
PV4-10RX-E	4 .050 Stock	Yellow	.515	#10	1.87	.55	.53	1.60	20	200	200	1200
PV4-14RX-E		Yellow	.515	1/4"	1.87	.55	.53	1.60	20	200	200	1200
PV4-56RX-E		Yellow	.515	5/16"	1.94	.68	.53	1.60	20	200	200	1200
PV4-38RX-E		Yellow	.515	3/8"	1.94	.68	.53	1.60	20	200	200	1200
PV4-12RX-E	Yellow	.515	1/2"	2.03	.86	.53	1.60	20	200	200	1200	
PV2-10RX-X	2 .060 Stock	Red	.610	#10	1.95	.68	.57	1.61	10	100	200	1200
PV2-14RX-X		Red	.610	1/4"	1.93	.68	.57	1.61	10	100	200	1200
PV2-56RX-X		Red	.610	5/16"	1.93	.68	.57	1.61	10	100	200	1200
PV2-38RX-X		Red	.610	3/8"	1.94	.69	.57	1.61	10	100	200	1200
PV2-12RX-X		Red	.610	1/2"	2.20	.86	.57	1.61	10	100	200	1200
P8-8R-Q	8 .040 Stock	—	—	#8	1.12	.42	.43	.91	25	250	200	2000
P8-10R-Q		—	—	#10	1.14	.47	.43	.91	25	250	200	2000
P8-14R-Q		—	—	1/4"	1.14	.47	.43	.91	25	250	200	2000
P8-56R-Q		—	—	5/16"	1.25	.59	.51	.95	25	250	200	2000
P8-38R-Q		—	—	3/8"	1.25	.59	.51	.95	25	250	200	2000
P8-12R-Q	—	—	1/2"	1.36	.82	.51	.95	25	250	200	2000	
P6-8R-E	6 .045 Stock	—	—	#8	1.21	.47	.43	.97	20	200	200	2000
P6-10R-E		—	—	#10	1.21	.47	.43	.97	20	200	200	2000
P6-14R-E		—	—	1/4"	1.21	.47	.43	.97	20	200	200	2000
P6-56R-E		—	—	5/16"	1.33	.62	.51	1.02	20	200	200	2000
P6-38R-E		—	—	3/8"	1.33	.62	.51	1.02	20	200	200	2000
P6-12R-E	—	—	1/2"	1.43	.82	.51	1.02	20	200	200	2000	
P4-10R-E	4 .050 Stock	—	—	#10	1.40	.55	.50	1.12	20	200	200	2000
P4-14R-E		—	—	1/4"	1.40	.55	.50	1.12	20	200	200	2000
P4-56R-E		—	—	5/16"	1.46	.68	.50	1.12	20	200	200	2000
P4-38R-E		—	—	3/8"	1.46	.68	.50	1.12	20	200	200	2000
P4-12R-E	—	—	1/2"	1.55	.86	.53	1.12	20	200	200	2000	
P2-10R-X	2 .060 Stock	—	—	#10	1.46	.68	.58	1.12	10	100	200	2000
P2-14R-X		—	—	1/4"	1.46	.68	.58	1.12	10	100	200	2000
P2-56R-X		—	—	5/16"	1.46	.68	.58	1.12	10	100	200	2000
P2-38R-X		—	—	3/8"	1.46	.68	.58	1.12	10	100	200	2000
P2-12R-X		—	—	1/2"	1.55	.86	.58	1.12	10	100	200	2000
P8-8HDR-Q	8 .065 Stock	—	—	#8	1.12	.42	.43	.91	25	250	200	2000
P8-10HDR-Q		—	—	#10	1.14	.47	.43	.91	25	250	200	2000
P8-14HDR-Q		—	—	1/4"	1.14	.47	.43	.91	25	250	200	2000
P8-56HDR-Q		—	—	5/16"	1.25	.59	.51	.95	25	250	200	2000
P8-38HDR-Q		—	—	3/8"	1.25	.59	.51	.95	25	250	200	2000
P8-12HDR-Q	—	—	1/2"	1.36	.82	.51	.95	25	250	200	2000	
P6-8HDR-E	6 .065 Stock	—	—	#8	1.21	.47	.43	.97	20	100	200	2000
P6-10HDR-E		—	—	#10	1.21	.47	.43	.97	20	100	200	2000
P6-14HDR-E		—	—	1/4"	1.21	.47	.43	.97	20	100	200	2000
P6-56HDR-E		—	—	5/16"	1.33	.62	.51	1.02	20	100	200	2000
P6-38HDR-E		—	—	3/8"	1.33	.62	.51	1.02	20	100	200	2000
P6-12HDR-E	—	—	1/2"	1.43	.82	.51	1.02	20	100	200	2000	
P4-10HDR-E	4 .070 Stock	—	—	#10	1.40	.55	.50	1.12	20	100	200	2000
P4-14HDR-E		—	—	1/4"	1.40	.55	.50	1.12	20	100	200	2000
P4-56HDR-E		—	—	5/16"	1.46	.68	.50	1.12	20	100	200	2000
P4-38HDR-E		—	—	3/8"	1.46	.68	.50	1.12	20	100	200	2000
P4-12HDR-E		—	—	1/2"	1.55	.86	.53	1.12	20	100	200	2000

Order the number of pieces required in multiples of standard package quantities.
X = 10 pcs., E = 20 pcs., Q = 25 pcs., C = 100 pcs., T = 200 pcs., D = 500 pcs. and M = 1000 pcs.