





METAL LINE SWITCHES

	Illuminated Piezo switches and indicators			
MOUNTING DIAMETER	Ø16mm	Ø22mm	Ø22mm	Ø24mm
SWITCHING FUNCTION	N.O.		N.O.	N.O.
HOUSING MATERIAL	Aluminum anodized/ Stainless steel	Aluminum anodized/ Stainless steel	Aluminum anodized	Aluminum anodized/ Stainless steel
SWITCHING CURRENT MAX.		100 mA	100 mA	100 mA
SWITCHING VOLTAGE MAX.		60 VDC	60 VDC	60 VDC
IP / IK RATING	IP 67 / IK 02	IP 69K / IK 02	IP 69K / IK 02	IP 69K / IK 02
TEMPERATURE	-20°C to +60°C	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C
				
TYPE	Indicator	PSE M22	PSE M22R	PSE M24
TERMINALS				
FASTON	°	°		
PINS				
WIRE LEADS		x (200 mm)	*	x (200 mm)
ILLUMINATION	point ill. 2 VDC	point ill. 24 VDC	ring ill. (12) / 24 VDC	ring ill. 24 VDC
	All switches are supplied with nut and o-ring seal			
	Part number			
COLOR				
ALUMINUM NATURAL	1241.3033 LED red	1241.3020 LED red	1241.3259 LED red	*LED red
ALUMINUM NATURAL	1241.3034 LED green	1241.3089 LED green	1241.3260 LED green	*LED green
ALUMINUM NATURAL	1241.3035 LED yellow	1241.3047 LED yellow	1241.3261 LED red/ green	1241.3010 LED red/ green
ALUMINUM NATURAL		NEW 1241.3244 LED blue		
RED	1241.3036 LED red	1241.3066 LED red		
GREEN	1241.3037 LED green	1241.3167 LED green		
GOLD	1241.3038 LED yellow	1241.3222 LED yellow		
STAINLESS STEEL				*

° Standard version

* Various designs