





		Plugs	Connectors	Receptacles	
					
Configuration				HSF Series Basic Receptacle	HSA Series*
30 Amp	2P, 3W 3P, 4W	8407 8408	8443 8444	HSF8403 HSF8404	8403 8404
60 Amp	2P, 3W 3P, 4W	8417 8418†	8453 8454	HSF8413 HSF8414	8413 8414
100 Amp	3P, 4W	8428-72	8464-72	HSF8424-72	8424-72

Note:
Reverse service available by adding "R" suffix to catalog number. Solder lugs on 100 amp only.

Connectors – can be furnished with conduit adapters to accommodate rigid conduit or standard connectors for armored and non-metallic cable or flexible conduit. See page 93.

* Can be furnished with 45° angle adapter when specified on order. Add suffix -45 to catalog number.

Flap Covers are standard on all receptacles.

Std. Cable Bushing (see page 10 for other bushings)

Current Rating	Bushing	Max. AWG Size
30	7/8"	#8, -7 strand or flexible
60	1 3/16"	#4, -7 strand or flexible
100	1 1/2"	#2, -7 strand or flexible

Conduit Size

Current Rating	Std. Size	Max. Size
30	1"	1 1/4"
60	1"	1"
100	2"	2"

Cable Conduit Adapters: see page 93.

†Note: 9418/F27194 Automotive 480VAC Version

Outlet Location: Standard Series

