

Thin Film Surface Mount Chip Attenuators

The **ims** A-Series thin film surface mount chip attenuator line is ideal for applications requiring precision attenuation in a small form factor packages. The attenuators are provided in the "π" configuration. Thin film technology insures a low noise, precise attenuator at a very affordable price. The wraparound terminations include a nickel barrier layer which affords excellent solderability and mechanical integrity. This chip attenuator line has the following features:

- Precision thin film attenuator element
- 99.5% Al₂O₃ substrate material
- Nickel barrier layer for excellent solderability and mechanical integrity
- Ultra low noise attenuator element
- Excellent high frequency performance
- Low inductance and parasitic capacitance
- Stable characteristics over temperature and time
- Polyimide passivation of attenuator element
- Available in bulk or on tape and reel



100% Matte Tin Finish

A-Series



Features

Thin film technology

Full Wraparound


Nickel Barrier for excellent solderability

Attenuation from 0 dB to 10 dB in 1 dB increments, 16 dB (A-1206, A-1612), 20 dB (A-1612)


VSWR 1.5:1 max. (A-0402), 1.3:1 all others

Terminations

Full wraparound



A-0603,0805,1206,1612




A-0402WA

Attenuation Ranges

The A-Series is available in values from 0dB to 10 dB in 1 dB increments. Standard impedance is 50Ω.

Frequency Characteristics (A-0805)*




*Performs within spec to 20 GHz when mounted face down.

ims International Manufacturing Services, Inc.

50 Schoolhouse Lane
Portsmouth, RI 02871
Tel (401) 683-9700
Fax (401) 683-5571
e-mail: ims@ims-resistors.com
<http://www.ims-resistors.com>

Dimensions

Part Number	Length	Width	Height	Terminal
A-0402WA	0.039 ± .004	0.020 ± .004	0.014 max.	0.009 ± .002
A-0603 & IMS2533	0.063 ± .004	0.032 ± .004	0.020 max.	0.016 ± .006
A-0805 & IMS1141	0.079 ± .008	0.049 ± .008	0.020 max.	0.020 ± .008
A-1206	0.126 ± .008	0.063 ± .008	0.020 max.	0.039 ± .010
A-1612	0.165 ± .008	0.118 ± .008	0.020 max.	0.037 ± .008




A-0603, A-0805, A-1206


Characteristics

Operating Temperature	-55°C to +125°C
Impedance	50 Ω
Frequency range	DC to beyond 10 GHz (A-0402WA, A-0603, A-0805) DC to 3 GHz (A-1206) DC to 2 GHz (A-1612)
VSWR	1.3:1 maximum (except A-0402WA - 1.5:1)
Attenuation	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 16*, 20** dB
Attenuation tolerance	
A-0805, 1141, A-1206, A-1612	± 0.3 dB, ± 0.5 dB (1206 - 16 dB, 1612 - 16 dB, 20dB)
A-0402WA, A-0603, 2533	± 0.3 dB (0 - 3dB) ± 0.5 dB (4 - 7 dB) ± 1.0 dB (8 - 10 dB)

* A-1206, A-1612 only **A-1612 only



A-0402WA



A-1612

Specifications

Maximum Working Voltage	
A-0402WA	1.26WVDC
A-0603 & IMS2533	1.77WVDC
A-0805 & IMS1141	2.24WVDC
A-1206	2.50WVDC
A-1612	3.53WVDC
Rated Power (70°C)	
A-0402WA	32mW
A-0603 & IMS2533	63mW
A-0805 & IMS1141	100mW
A-1206	125mW
A-1612	250mW

Ordering Information

Face Up Example: 3 dB, 100 mW, SMT 0805 attenuator.

A	-0805	- C	-03DB
Prefix for Face Up Attenuator			Attenuation level 00 - 10 dB, 16*, 20**dB *A-1206 & 1612 only ** A-1612 only
Form factor			C indicates 50Ω impedance
0402WA, 0603, 0805, 1206, 1612			

Face Down Example: 3 dB, 100 mW, SMT 0805 attenuator.

IMS1141	- 03DB
IMS2533 = Face Down 0603 IMS1141 = Face Down 0805	Attenuation level 00 - 10 dB

For higher dB values, higher power ratings or lead content attenuators see our IAX Series

Ask Us About Engineering Kits!

ims International Manufacturing Services, Inc.

50 Schoolhouse Lane
Portsmouth, RI 02871
Tel (401) 683-9700
Fax (401) 683-5571
e-mail: ims@ims-resistors.com
<http://www.ims-resistors.com>