


# IDK-1110W

## 10.1" WSVGA Industrial Display kit with Touch Solution

NEW



### Features

- 10.1" LCD supports 1024 x 600 pixels and wide operating temperature (-5~ 60° C)
- Brightness of 550 cd/m<sup>2</sup> with LED backlight
- 4-wire resistive touch solution
- High contrast ratio of 500:1
- High uniformity of 85%
- LVDS signal interface
- Low power consumption 8.99 W (panel only)
- LED driver board built in
- Touch controller included (USB)
- AR surface treatment (optional)
- Optical bonding (optional)

### Introduction


The Advantech IDK-1110W series comes with a 10.1" industrial grade LCD display with 4-wire resistive touch. The series is also available with flexible options for LCD screens enhanced treatment such as Anti-Reflection surface treatment and optical bonding solution. IDK-1110W series supports 4-wire resistive touch with low power consumption at the maximum of 8.99 W. IDK-1110W series is ideal for embedded applications which customers have maximum flexibility for mechanical design.

### Specifications

Display	Display Size	10.1" LED backlight panel (WSVGA)
	Resolution	1024 x 600
	Viewing Angle (U/D/L/R)	70° / 50° / 70° / 70°
	Brightness	550 cd/m <sup>2</sup>
	Backlight Life (hrs)	50,000hrs
	Contrast Ratio	500 : 1
	Response Time (ms)	25 ms
	Colors	6 Bit (262K)/8 bit (16.2 M)
	Voltage	3.3 V Power
	Consumption	8.99 W
	Signal Interface	1 channel LVDS
	Weight	420 g
	Dimensions (W x H x D)	235 x 145.8 x 10.25 mm
Touchscreen	Touch Screen	4-wire Resistive
	Transparency	82.5± 2.5%
	Surface Hardness	3H
	Durability	1 million times
Environment	Operating Temperature	-5 ~ 60° C
	Storage Temperature	-20 ~ 70° C
	Humidity	10 ~ 90% @ Max. 25° C, non-condensing

## Dimensions

Unit: mm



## Ordering Information

Part No.	Size	Brightness (cd/m <sup>2</sup> )	Interface	Touch screen	Touch Interface
IDK-1110WR-55WSA1E	10.1"	550	LVDS	4-wire Resistive	USB

## Packing List

Part Number	Description
ETM-RES05C-EEH4EE	1 x 4-wire USB Touch controller
1700020324-01	1 x USB Touch cable 5P-2.0/USB-A (M) 180CM

Note: Package contents are subject to change without prior notice

## Optional Order

SBC Part No.	LVDS cable P/N	Display interface	B/L cable P/N	Touch interface	Touch power input
MIO-5250	96CB-L3040PIE4	LVDS: Single channel 18bit (WSVGA)	96CB-E0405PIE3	USB	5 V
PCM-9363	96CB-L3020PIE2	LVDS: Single channel 18bit (WSVGA)	96CB-E0405PIE3	USB	5 V
AIMB-270	96CB-L3020PIE2 (20pin) 96CB-L3040PIE4 (40pin)	LVDS: Single channel 18bit (WSVGA)	96CB-E0405PIE3	USB	5 V

For more compatible embedded board solution, please visit our Build Your display web page as below  
<http://www.advantech.com/buildyourdisplay>