

1374898-1 Product Details

 [Live Product Chat](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)



1374898-1

TE Internal Number: 1374898-1



Obsolete

[Contact Product Information Center](#)

Fiber Optic Cable Assemblies - Obsolete

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- Cable Assembly
- Cable Assembly Type = LIGHTRAY MPX (Female) to LIGHTRAY MPX (Female)
- LIGHTRAY Connector
- Fiber Type = SM
- Singlemode

[View all Features](#)



[Add to My Part List](#)



[Request Sample](#)



[Find Similar Products](#)



[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Cable Assembly
- Cable Assembly Type = LIGHTRAY MPX (Female) to LIGHTRAY MPX (Female)
- Connector = LIGHTRAY
- Industry Application = Fiber Optics (Multi-User), Networking (Communications)
- [Product Designation](#) = LIGHTRAY

Mechanical Attachment:

- AMP Logo = With

Termination Related Features:

- Mode = Singlemode
- Insertion Loss (dB) = 1.00

Body Related Features:

- [Fiber Type](#) = SM
- Cable Diameter (mm [in]) = 2.20 x 4.00 [.087 x .157]
- Number of Fibers = 4
- Flammability Rating = Riser (UL OFNR/CSA FT-4)
- Cable Color = Yellow
- Length (M [ft]) = 6.00 [19.68]
- Ferrule Material = Glass Filled Epoxy

Contact Related Features:

- Mode Conditioned Launch Cable Assembly = No
- Boot Body Style - Left = Standard
- Boot Color - Left = Black
- Boot Body Style - Right = Standard
- Boot Color - Right = Black
- Fibre Channel = No

Configuration Related Features:

- Cable Type = Ribbon Fiber
- Cable Buffering = Tight
- Connector(s) Exit Angle to Connector(s) Exit Angle = 180? to 180?

Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process

Other:

- Brand = AMP