



A POWERHOUSE

SMALL SIGNAL

H-SOT SURFACE MOUNT NPN TRANSISTORS

PACKAGE	DEVICE TYPE	V_{CE0} VOLTS	PEAK I_C mA	h_{FE} min/max	$I_C @ V_{CE}$ mA V	$V_{CE (sat)}$ max VOLTS	$I_C @ I_B$ mA mA
3 PIN CERAMIC LCC 	SLC918	15	50	20 min	3.0/1.0	0.4	10.0/1.0
	SLC930	15	30	20-200	3.0/1.0	0.4	10.0/1.0
	SLC2221A	40	800	40-120	150.0/10.0	0.3	150.0/15.0
	SLC2222A	40	800	100-300	150.0/10.0	0.3	150.0/15.0
	SLC2369A	15	200	30 min	3.0/0.4	0.2	10.0/1.0
	SLC2484	60	50	100-500	0.01/5.0	0.35	1.0/0.1
	SLC3903	40	200	50-150	10.0/1.0	0.2	10.0/1.0
	SLC3904	40	200	100-300	10.0/1.0	0.2	10.0/1.0
	SLC4123	30	200	50-150	2.0/1.0	0.3	50.0/5.0
	SLC4124	25	200	120-360	2.0/1.0	0.3	50.0/5.0
	SLC5088	30	100	300-900	0.1/5.0	0.5	10.0/1.0
	SLC5550	140	600	60-250	10.0/5.0	0.15	10.0/1.0
	SLC5551	160	600	80-250	10.0/5.0	0.15	10.0/1.0

DUAL CHIP SURFACE MOUNT NPN TRANSISTOR

6 PIN DUAL CERAMIC LCC 	SLD2222A	40	800	40-120	15.0/10.0	0.3	150.0/15.0
	SLD2369A	15	200	30 min	30.0/0.4	0.2	10.0/1.0
	SLD2484	60	50	100-500	0.01/5.0	0.35	1.0/0.1
	SLD3903	40	200	50-150	10.0/1.0	0.2	10.0/1.0
	SLD3904	40	200	100-300	10.0/1.0	0.2	10.0/1.0

- Electrical Characteristics at 25° C unless otherwise noted
- Specifications per transistor