



SS1020FL~SS10100FL

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

VOLTAGE 20 to 100 Volts **CURRENT** 1.0 Amperes


SOD-123FL Unit: inch (mm)

FEATURES

- Fast switching speed
- Surface mount package ideally suited for automatic insertion
- Low power loss, high efficiency
- In compliance with EU RoHS 2002/95/EC directives

MECHANICAL DATA

- Case: SOD-123FL, Plastic
- Terminals: Solderable per MIL-STD-750, Method 2026
- Weight: 17.25mg
- Polarity : Color band denotes cathode end



ABSOLUTE RATINGS

PARAMETER	Symbol	SS1020FL	SS1030FL	SS1040FL	SS1060FL	SS10100FL	UNITS
Marking Code	-	G2	G3	G4	G6	G10	-
Reverse Voltage	V_R	20	30	40	60	100	V
Peak Reversr Voltage	V_{RRM}	20	30	40	60	100	V
Average Rectified Cuttent at $T_A=75\text{ C}$	$I_{F(AV)}$	1.0					A
Non-repetitive Peak Forward Surge Current at $t=8.3\text{ms}$	I_{FSM}	40					A

ELECTRICAL AND THERMAL CHARACTERISTICS

PARAMETER	Symbol	SS1020FL	SS1030FL	SS1040FL	SS1060FL	SS10100FL	UNITS
Junction Temperature	T_J	125					°C
Storage Temperature	T_{STG}	-50 to +125					°C
Minimum Reverse Breakdown Voltage at $I_R=500\mu\text{A}$	V_R	20	30	40	60	100	V
Maximum Forward Voltage at $I_F=1.0\text{A}$	V_F	0.55	0.55	0.55	0.70	0.85	V
Reverse Leakage Current at V_{RRM}	I_R	500					μA
Typical Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	88					°C/W
Typical Junction Capacitance Rating at $V_R=0\text{V}$	C_J	60	60	60	50	40	pF





Note.1 Mounted with minimum recommended pas size, PC Board FR4.

2. $T_A=25^\circ\text{C}$ unless otherwise specified.



SS1020FL~SS10100FL


Rating and Characteristic Curves





SS1020FL~SS10100FL

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 10K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2009

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.