





PRODUCT NUMBER	PICK-UP CAP			3	4	
	(NATURAL OR BLACK IN COLOR)	CONTACT PLATING AND THICKNESS	SOLDER BALL	NOTES		
84500-002	YES	15µ" (.38µm) Au	SnPb			
84500-002LF	YES	15µ" (.38µm) Au	LEAD FREE	7 & 8		
84500-092	YES	15μ" (.38μm) GXT	SnPb			
84500-092LF	YES	15μ" (.38μm) GXT	LEAD FREE	7 & 8		
84500-102	YES	30µ" (.76µm) Au	SnPb			
84500-102LF	YES	30μ" (.76μm) Au	LEAD FREE	7 & 8		
84500-192	YES	30µ" (.76µm) GXT	SnPb			
84500-192LF	YES	30µ" (.76µm) GXT	LEAD FREE	7 & 8		
84500-202	YES	50μ" (1.27μm) Au SPECIAL	SnPb	4, & 5		
84500-202LF	YES	50μ" (1.27μm) Au SPECIAL	LEAD FREE	4, 5, 7 & 8		
84500-292	YES	50μ" (1.27μm) GXT SPECIAL	SnPb	4, & 5		
84500-292LF	YES	50μ" (1.27μm) GXT SPECIAL	LEAD FREE	4, 5, 7, & 8		А
84500-A02	YES	30μ" (.76μm)	SnPb	9		
84500-A02LF	YES	30µ" (.76µm)	LEAD FREE	7, 8 & 9		
-84500-302	YES	15µ" (.38µm) Au SPECIAL	SnPb	9—		
-84500 302LF	YES	15µ" (.38µm) Au SPECIAL	LEAD FREE	8 & 9		
84500-402	YES	30µ" (.76µm) Au SPECIAL	SnPb	9-		
84500-402LF	YES	30μ" (.76μm) Au SPECIAL	LEAD FREE	8 & 9		
84500 502	YES	Au SPECIAL	SnPb	4, 5 & 9		
84500-502LF	YES	Au SPECIAL	LEAD FREE	4, 5, 8, & 9		
form: A4mmXLc	1 T	Ltr et N Sheet index	SEE NOTE 1 ASME Y14.5 \(\sqrt{ASME} \) ASME on no dr date toterances unless otherw angles \(\frac{1}{2} \) \(\text{XXX} \) \(\text{Or} \text{\$\frac{1}{2}\$} \) \(\text{XXX} \) \(\text{Or} \text{\$\frac{1}{2}\$} \) \(\text{XXX} \) \(\text{Or} \text{\$\frac{1}{2}\$} \) \(\text{BREWBAKER} \) \(\text{Chr} \text{\$\frac{1}{2}\$} \) \(\text{BREWBAKER} \)	Y14.5 ise specified	0mm PLUG ASSEMBLY X 30 = 300 POSITIONS 10 Sheet 4 of 5 size 84500 A4	e 4
	84500-192 84500-192LF 84500-202 84500-292LF 84500-292LF 84500-A02 84500-A02LF 	84500-192 YES 84500-192LF YES 84500-202 YES 84500-202LF YES 84500-292 YES 84500-292LF YES 84500-A02 YES 84500-A02 YES 84500-302 YES	84500-192 YES 30μ" (.76μm) GXT 84500-192LF YES 30μ" (.76μm) GXT 84500-202 YES 50μ" (1.27μm) Au SPECIAL 84500-202LF YES 50μ" (1.27μm) GXT SPECIAL 84500-292 YES 50μ" (1.27μm) GXT SPECIAL 84500-292LF YES 30μ" (.76μm) 84500-A02 YES 30μ" (.76μm) 84500-A02LF YES 30μ" (.76μm) 84500-302 YES 15μ" (.38μm) Au SPECIAL -84500-302LF YES 15μ" (.38μm) Au SPECIAL -84500-402 YES 30μ" (.76μm) Au SPECIAL -84500-402LF YES 30μ" (.76μm) Au SPECIAL -84500-502 YES Au SPECIAL -84500-502LF YES Au SPECIAL -84500-502LF YES Au SPECIAL	S4500-192	S4500-192 YES 30μ" (.76μm) GXT LEAD FREE 7 & 8	84500-192

PDM: Rev:N STATUS: Released Printed: Nov 14, 2012

3 1

PRODUCT NUMBER SEE TABLE

NOTES:

MATERIAL:

HOUSING: LCP

CONTACT: COPPER ALLOY

PLATING:

CONTACT: (SEE TABLE) SOLDER BALL: (SEE TABLE) EUTECTIC SnPb OR LEAD FREE 95.5Sn/4Ag/0.5Cu

- SOLDER BALLS WILL NOT BE PERFECT SPHERICAL SHAPE DUE TO REFLOW ATTACHMENT.
- MATED HEIGHT EFFECTED BY CUSTOMER'S PCB PAD SIZE, PLATING, SOLDER REFLOW PROFILE, & SOLDER PASTE.

1 | 2

- (4.) PLATING FOR INDICATED -2XX SERIES PRODUCT NUMBERS MEET THE REQUIREMENTS OF (GR-1217-CORE, CENTRAL OFFICE ENVIRONMENT, 25 YEAR LIFE EXPECTANCY).
- 5.) PLATING FOR INDICATED -2XX SERIES PART NOS. IS AU OVER NI WITH SPECIAL CONTACT GEOMETRY TO MEET REQUIREMENTS OF TELCORDIA GR-1217-CORE: CENTRAL OFFICE ENVIRONMENT.
- KNIT LINE: SLIGHT VISIBLE MARKS (USUALLY A LINE) INDICATING THE DIRECTION AND MEETING POINT OF PLASTIC RESIN FLOW FRONTS TRAVELING AROUND ANY OBSTRUCTIONS TO THE RESIN FLOW VIA THE REQUIRED MOLD TOOLING.

- FOR PROPER APPLICATION FOLLOW FCI APPLICATION SPECIFICATION GS-20-033 LEAD FREE SOLDER BALLS WILL NOT SOLDER PROPERLY IN A LEADED SOLDER PROCESS DUE TO A HIGHER REFLOW TEMPERATURE. LEAD FREE PRODUCT IS THERFORE NOT BACKWARDS COMPATIBLE WITH LEADED OR SOME SOLDERING APPLICATIONS. REFERENCE FCI APPLICATION SPECIFICATION.
- (8.) THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-47-0004 PRODUCT MEETING THIS DIRECTIVE IS IDENTIFIED IN THE LOT CODE NUMBER MARKED ON EACH PART BY HAVING AN "X" IN THE SEVENTH CHARACTER POSITION.
- (9.) 84500-A02 AND -A02LF ARE CUSTOMER SPECIALS.
- (10.) CURRENT COMPANY LOGO TO BE VISIBLE IN APPROXIMATE AREA SHOWN.

11. A M SYMBOL WILL BE NEXT TO ANY DIMENSION, NEW VIEW OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION

mat'l. code				surfa	surface / tol			lerance		projection		product family										
SEE NOTE 1			ASME Y14.5 V ASME Y			Y14.5		⊕ -⊖			MEG-ARRAY											
ltr	ecn n	o dr	0	date	tolera	tolerances unless otherw				wise specified		P-5		title								
N			\perp		angle	, i		.X	E.±X.		ММ		0mm PLUG ASSEMBLY									
					anyu	angles E		.XX±.13		-										c		
					0° ±	2*		XXX.	±.051		scale		2:1	10	$10 \times 30 = 300 \text{ POSI}$					ПОІ	12	
					dr	T. 8	BREWB	REWBAKER 2011-		-06		_	dwg	по			S	heet	5 0	f 5	size	
					engr	Т. Е	BREWB	AKER	2011-06-06		JFC		, Î.,		84500 A ₄							
					chr	Т. Е	BREWB	REWBAKER 2011 HORCHLER 2011		2011-06-06				$\frac{64300}{100}$							Α4	
					appd	D.	HORCH			-06				type			CUSTOMER Draw				ing	
shee	n te	evision																				
index	× [5	sheet	Т																			

3

form: A4mmXLc

1

PDM: Rev:N