

Product Information

ISSUE DATA : 2006-06-01

MODEL : LTV350QV-F0E

**Note : The Product and specifications are subject to change without any notice.
Please ask for the latest Product Standards to guarantee the satisfaction of
your product requirements.**

PREPARED BY : AMLCD Mobile Display Development

LCD DIVISION

Samsung Electronics Co., Ltd.



Contents

General Description	-----	(5)
1. Absolute Maximum Ratings	-----	(6)
1.1 Absolute Ratings Of Environment		
1.2 Electrical Absolute Ratings		
2. Optical Characteristics	-----	(8)
3. Electrical Characteristics	-----	(12)
3.1 TFT-LCD Module		
3.2 Back-light Unit		
4. Touch Screen Panel Specification	-----	(14)
4.1 Electrical Characteristics		
4.2 Mechanical & Reliability Characteristics		
4.3 Integration Design Guide		
5. Block Diagram	-----	(17)
5.1 TFT-LCD Module(Interface System Structure) with Back Light Unit		
5.2 Touch Screen Panel		
5.3 Back-light Unit		
6. Input Terminal Pin Assignment	-----	(19)
6.1 Input Signal & Power		
6.2 Back-Light Unit		
6.3 Touch screen panel		
6.4 Input Signal, Basic Display colors and Gray Scale of Each Colors		
7. Operation Specifications	-----	(22)
7.1 Serial Peripheral Interface		
7.2 Data Format for 24bit RGB Interface		
7.3 24bit RGB Interface Timing		
7.4 Electrical Specifications		
8. Command List & Instruction Descriptions	-----	(27)
8.1 Command List		
8.2 Instruction Descriptions		
9. Power On/Off Sequence	-----	(28)
9.1 Power On Sequence		
9.2 Power Off Sequence		
10. Reliability Test Result	-----	(32)
11. Outline Dimension	-----	(33)
12. Packing	-----	(35)
13. Marking & Others	-----	(36)

14. General Precaution

----- (37)

14.1 Handling

14.2 Storage

14.3 Operation

14.4 Others

General Description

* Description

LTV350QV-F0E is a TMR(Transmissive with Micro Reflective) type color active matrix TFT (Thin Film Transistor) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching devices. This model is composed of a TFT-LCD module, a driver circuit and a back-light unit and a touch screen panel(TSP).

The resolution of a 3.5" contains 320RGBx240 dots and can display up to 16.7M colors.

* Features

- Transmissive with Micro Reflective type and back-light with six LEDs are available.
- Using the Touch Screen Panel(Film to Film-Glass type).
- TN(Twisted Nematic) mode.
- Line inversion mode with stripe type.
- 24bit RGB Interface + Serial Peripheral Interface(SPI)
- SYNC(Vsync, Hsync, Dotclk) mode
- Gate Driver IC embeded on Panel(Double ASG)

* Applications

- Display terminals for DSC(Digital Still Camera), PMP(Portable Multimedia Player) application products.

* General information

Items	Specification	Unit	Note
Display area	70.08(H) x 52.56(V)	mm	-
Driver element	a-Si TFT active matrix	-	-
Display colors	16.7M	colors	-
Number of pixels	320RGB(H) x 240(V)	dot	-
Pixel arrangement	stripe type	-	-
Pixel pitch	0.219(H) x 0.219(V)	mm	-
Display mode	Normally White	-	-
Viewing direction	6	o'clock	-

* Mechanical information

Item		Min.	Typ.	Max.	Unit	Note
Module size	Horizontal(H)	76.70	76.90	77.10	mm	-
	Vertical(V)	63.70	63.90	64.10	mm	(1)
	Depth(D)	4.05	4.25	4.45	mm	(1)
Weight		-	43	48	g	-

Note (1) Not include FPC.

Refer to the Outline Dimension in the "11.Outline Dimension" for further information.

(2) Touch Screen Panel and Back-light unit are included.


1. Absolute Maximum Ratings

1.1 Environment

ITEM	MIN	MAX	REMARK
Storage Temperature	-30°C	70°C	Note(1)
Operating Temperature	-20°C	60°C	Note(2)(3)

Note(1) 90%RH maximum humidity, 60°C maximum wet-bulb temperature

- (2) When operated at a temperature lower than 0°C,
the LCD worked slowly and the screen appeared low-contrast images
due to the characteristics of LC(Liquid Crystal).
- (3) If any fixed pattern is displayed on LCD for minutes,
image-sticking phenomenon may occur.



Temperature & Humidity Graph at Absolute Environment

1.2 Electrical Absolute Ratings**(1) TFT-LCD Module**(Ta = 25 ± 2°C, V_{ss}=GND=0)

Characteristics	Symbol	Min.	Max.	Unit	Note
Digital supply voltage	V _{CC}	-0.3	5.0	V	-
Analog supply voltage	DDVDH	-0.3	7.0	V	-
Gate On voltage	V _{GH}	-0.3	22.0	V	-
Gate Off voltage	V _{GL}	-18.5	0.3	V	-

(2) Back-Light Unit

(Ta = 25 ± 2°C)

Item	Symbol	Min.	Max.	Unit.	Note
Current	I _B		25	mA	(1)

Note (1) Permanent damage to the device may occur if maximum values are exceeded or reverse voltage is loaded.

Functional operation should be restricted to the conditions described under normal operating conditions.

2. Optical Characteristics

The following items are measured under stable conditions. The optical characteristics should be measured in a dark room or equivalent state with the methods shown in Note (1).

Measuring equipment: LCD-5000, BM-5A, BM-7, PR-650, EZ-Contrast

(Ta = 25 ± 2°C, V_{CC} = V_{CI} = 3.3V, I_B = 20mA)


Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Contrast ratio (Center point)		C/R	NOTE (1)	150	300	-	-	(2) BM-5A
Luminance of white (Center point)		Y _L		260	320	-	cd/m ²	(3) BM-5A
Response time	Rising:Tr	Tr+Tf		φ = 0 θ = 0	-	25	30	msec
	Falling:Tf							
Color chromaticity (CIE 1931)	White	W _x	Normal Viewing Angle B/L On	0.28	0.33	0.38	-	(5) PR-650
		W _y		0.32	0.37	0.42		
	Red	R _x		0.56	0.61	0.66		
		R _y		0.31	0.36	0.41		
	Green	G _x		0.28	0.33	0.38		
		G _y		0.55	0.60	0.65		
	Blue	B _x		0.10	0.15	0.20		
		B _y		0.10	0.15	0.20		
Viewing angle	Hor.	θ _L	C/R≥10 B/L On	55	60		Degrees	(6) Ez-Contrast
		θ _R		55	60			
	Ver.	φ _H		45	50			
		φ _L		50	55			

Note (1) Test Equipment Setup


After stabilizing and leaving the panel alone at a given temperature for 30 min , the measurement should be executed. Measurement should be executed in a stable, windless, and dark room. 30 min after lighting the back-light. This should be measured in the center of screen.

Environment condition : $T_a = 25 \pm 2 \text{ }^{\circ}\text{C}$

Back-Light On condition



Back-Light Off condition



Optical Measuring Equipment Setup

Note (2) Definition of Contrast Ratio (C/R) : Ratio of gray max (Gmax) & gray min (Gmin) at the center point


$$CR = \frac{G_{\max}}{G_{\min}}$$

* Gmax : Luminance with all pixels white

* Gmin : Luminance with all pixels black

Note (3) Definition of Luminance of White : Luminance of white at the center point


Note (4) Definition of Response time : Sum of T_r , T_f



Note (5) Definition of Color Chromaticity (CIE 1931)

Color coordinate of white & red, green, blue at center point.

Note (6) Definition of Viewing Angle : Viewing angle range ($CR \geq 10$)



3. Electrical Characteristics

3.1 TFT-LCD Module

Ta = 25 ± 2°C


Characteristics		Symbol	Min.	Typ.	Max.	Unit	Note
Digital supply voltage		V _{CC}	2.5	3.3	3.6	V	-
Analog supply voltage		DDVDH	4.8	4.9	5.0	V	-
Gate On voltage		V _{GH}	17.0	18.0	19.0	V	#1
Gate Off voltage		V _{GL}	-11	-10	-9	V	-
Vcom High voltage		VcomH		3.68			
Vcom Low voltage		VcomL		0.4			
Power Dissipation	Full	P _{FULL}		40	60	mW	#2,#3
Frame frequency		f _{Frame}	60	75	90	Hz	-
Dot Clock		DOTCLK	-	-	10.0	MHz	-
Serial Clock		SCL	-	-	16.0	MHz	-

Note #1. $|V_{GH} - (V_{GL} \times 0.7)| = 25V$

Note #2. V_{CC} = 3.3V, f_{Frame} = 75Hz, DOTCLK = 7.0MHz

Note #3. Dissipation current check pattern

► 0 Gray black pattern



3.2 Back-Light unit

The back-light system is an edge-lighting type with **six** white LED(Light Emitting Diode)s.


(Ta=25 ± 2°C)

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Current	I_B	-	20	-	mA	(1)
Power Consumption	P_{BL}	-	400	-	mW	(2)

Note (1) **Six** LEDs serial type.

(2) Where $I_B = 20\text{mA}$, $V_B = P_{BL} / I_B$

■ Ambient Temperature vs. Allowable Forward Current



4. Touch Screen Panel Specifications

4-1. Electrical Characteristics

Item	Min.	Typ.	Max.	Unit	Note
Linearity	-1.5	-	1.5	%	Analog X and Y directions
Terminal resistance	200	460	900	Ω	X(Film side)
	200	350	900	Ω	Y(Film side)
Insulation resistance	25	-	-	M Ω	DC 25V
Voltage	-	-	7	V	DC
Chattering	-	-	10	ms	100k Ω pull-up
Transparency	78	80	-	%	Non-glare

Caution (1) : Do not operate it with a thing except a polyacetal pen(tip R0.8mm or less) or a finger, especially those with hard or sharp tips such as a ball point pen or a mechanical pencil.

4-2. Mechanical & Reliability Characteristics

Item	Min.	Typ.	Max.	Unit	Note
Activation force	5		80	g	(1)
Durability-surface scratching	Write 100,000	-	-	characters	(2)
Durability-surface pitting	1,000,000	-	-	touches	(3)
Surface hardness	3	-	-	H	JIS K5400, ASTM D3363

Note (1) Stylus pen Input : R0.8mm polyacetal pen or Finger

(2) Measurement for Surface area


- Scratch 100,000 times straight line on the Film with a stylus change every 20,000times
- Force : 250gf
- Speed : 60mm/sec
- Stylus : R0.8 polyacetal tip

(3) Pit 1,000,000 times on the Film with a R8.0 silicon rubber.


- Force : 250gf
- Speed : 2times/sec

4-3. Integration Design Guide

- Avoid the design that Front-case overlap and press on the active area of the touch-panel.
- Give enough gap (over 0.5mm at compressed) between the front case and touch-panel to protect wrong operating.




- Use a buffer material(Gasket) between the touch-panel and Front-case to protect damage and wrong operating.
- Avoid the design that buffer material overlap and press on the inside of touch-panel viewing area.




Left side

Right side



Bottom side


Top side




GENERAL TOLERANCE				2005.05.11		APPLIED SAMSUNG FORM							
STEP	LEVEL 1	LEVEL 2	LEVEL 3	REV	DATE	DESCRIPTION OF REVISION				REASON			CHG'D BY
0 < X ≤ 4	±0.05	±0.1	±0.2	UNIT	mm	DRA'N BY	DES'D BY	CHK'D BY	APP'D BY	MODEL NAME			
4 < X ≤ 16	±0.08	±0.15	±0.3	SCALE	Free					PART/SHEET NAME		D402C	SHEET 2/2
16 < X ≤ 64	±0.12	±0.20	±0.5	TOLERANCE LEVEL 1									
64 < X ≤ 256	±0.25	±0.4	±0.8	SAMSUNG ELECTRONICS						SPEC. NO.		CODE NO.	VER.

5. Block Diagram

5.1 TFT-LCD Module (Interface System Structure) with Back Light Unit




5.2 Touch Screen Panel



Top View

X : Upper electrode
Y : Lower electrode

5.3 Back-light Unit



Pin No.	Symbol	I/O
1	LED_ANODE	Anode
2	LED_CATHODE	Cathode

6. Input Terminal Pin Assignment

6.1 Input Signal & Power (Connector type : 60Pin / 0.5mm pitch / Bottom contact)

- IRISO ; 9634Series, HIROSE : FH12-60S-0.5SV

No	Symbol	Description	I/O	No	Symbol	Description	I/O
1,2	LED__Cathode	LED__Cathode	I	29	DATA11	Green data	I
3,4	LED__Anode	LED__Anode	I	30	DATA12	Green data	I
5	GND	Ground	I	31	DATA13	Green data	I
6	X1	X_Right	I	32	DATA14	Green data	I
7	Y1	Y_Bottom	I	33	DATA15	Green data(MSB)	I
8	X2	X_Left	I	34	DATA16	Red data(LSB)	I
9	Y2	Y_Up	I	35	DATA17	Red data	I
10	GND	Ground	I	36	DATA18	Red data	I
11	C6(1uF,10V)	Stable Capacitor connection	O	37	DATA19	Red data	I
12	C5(1uF,10V)	Stable Capacitor connection	O	38	DATA20	Red data	I
13	M	The signal to generate Vcom	O	39	DATA21	Red data	I
14	RESET	Reset	I	40	DATA22	Red data	I
15	CS	Chip Select	I	41	DATA23	Red data(MSB)	I
16	SCL	Serial Clock	I	42	HSYNC	Horizontal Synchronous Signal	I
17	SDI	Serial Data	I	43	VSYNC	Vertical Synchronous Signal	I
18	DATA0	Blue data(LSB)	I	44	DOTCLK	Data Clock	I
19	DATA1	Blue data	I	45,46	AVDD	Vanalog	I
20	DATA2	Blue data	I	47,48	VDD	Vdigital	I
21	DATA3	Blue data	I	49	C4(1uF,10V)	Stable Capacitor connection	O
22	DATA4	Blue data	I	50,51	VGL	Vgoff voltage	I
23	DATA5	Blue data	I	52	C3(1uF,10V)	Stable Capacitor connection	O
24	DATA6	Blue data	I	53	VGH	Vgon Voltage	I
25	DATA7	Blue data(MSB)	I	54	C2(1uF,10V)	Stable Capacitor connection	O
26	DATA8	Green data(LSB)	I	55	C1(1uF,10V)	Stable Capacitor connection	O
27	DATA9	Green data	I	56,57	VCOM	VCOM	I
28	DATA10	Green data	I	58,59,60	GND	Ground	I

6.2 Back-Light Unit (Connector : 2 pin FPC Solder type)

Pin No.	Symbol	Function
1	LED_ANODE	LED Anode
2	LED_CATHODE	LED Cathode

6.3 Touch Screen Panel (Connector : 4Pin FPC Solder type)

Pin No.	Symbol	I/O	Function
1	X1	Right	Right electrode - differential analog
2	Y1	Bottom	Bottom electrode - differential analog
3	X2	Left	Left electrode - differential analog
4	Y2	Top	Top electrode - differential analog

6.4 Input Signal, Basic Display Colors and Gray Scale of Each Colors

COLOR	DISPLAY	DATA SIGNAL																											GRAY SCALE LEVEL
		RED									GREEN								BLUE										
		R0	R1	R2	R3	R4	R5	R6	R7	G0	G1	G2	G3	G4	G5	G6	G7	B0	B1	B2	B3	B4	B5	B6	B7				
BASIC COLOR	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-		
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	-		
	GREEN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	-		
	CYAN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-		
	RED	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-		
	MAGENTA	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	-		
	YELLOW	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	-		
	WHITE	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-		
GRAY SCALE OF RED	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R0		
	DARK ↑	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1		
		0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R2		
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	R3-R252		
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:				
	LIGHT ↓	1	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R253		
		0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R254		
	RED	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R255		
GRAY SCALE OF GREEN	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G0		
	DARK ↑	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G1		
		0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G2		
		:			:	:	:	:	:	:			:	:	:	:	:	:			:	:	:	:	:	:	G3-G252		
		:			:	:	:	:	:	:			:	:	:	:	:	:			:	:	:	:	:				
	LIGHT ↓	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	G253		
		0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	G254		
	GREEN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	G255		
GRAY SCALE OF BLUE	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	B0		
	DARK ↑	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	B1		
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	B2		
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	B3-B252		
		:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:				
	LIGHT ↓	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	1	B253		
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	B254		
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	B255		


Note) Definition of Gray :

Rn : Red Gray, Gn : Green Gray, Bn : Blue Gray (n = Gray level)

Input Signal : 0 = Low level voltage, 1 = High level voltage


7. Operation Specifications

7.1 Serial Peripheral Interface




(Note) RS="0": Index data
RS="1": Instruction data

7.2 Data Format for 24bit RGB Interface



7.3 24bit RGB Interface Timing - SYNC mode



$$\begin{aligned} * \text{DOTCLK} &= f_{\text{frame}} \times (240 + VBP + VFP) \times (320 + HBP + HFP) \\ &= 75\text{Hz} \times (240 + VBP + VFP) \times (320 + HBP + HFP) \end{aligned}$$

- * $3H \leq VFP$
- * $HBP > HLW$
- * $VBP > VLW$
- * $15clk < HLW < 20clk$
- * $VLW > HLW$


Note 1. Polarity register setting : VPL = 0, HPL = 0, DPL=0
2. The rising edge of DOTCLK is used to fetch display data

7.4 Electrical Specifications

a. RGB Data Interface Characteristics

(T_A = -40 to +85°C)

Characteristic	Symbol	24bit RGB Interface		Unit
		Min	Max	
DOTCLK cycle time	tDCYC	100	-	ns
DOTCLK rise/fall time	tR,tF	-	10	
DOTCLK Pulse width high	tDCHW	50	-	
DOTCLK Pulse width low	tDCLW	50	-	
SYNC setup time	tSYS	30	-	
SYNC hold time	tSYH	30	-	
PD data setup time	tPDS	30	-	
PD data hold time	tPDH	30	-	




AC Characteristics

b. Clock Synchronized Serial Mode Characteristics

(T_A = -40 to +85°C)

Characteristic	Symbol	Min	Max	Unit
Serial clock cycle time	tscyc	100	-	ns
Serial clock rise/fall time	tR,tF	-	10	
Pulse width high for write	tSCHW	30	-	
Pulse width high for read	tSCHR	50	-	
Pulse width low for write	tSCLW	30	-	
Pulse width low for read	tSCLR	50	-	
Chip Select setup time	tCSS	20	-	
Chip Select hold time	tCSH	50	-	
Serial input data setup time	tSIDS	30	-	
Serial input data hold time	tSIDH	30	-	
Serial output data delay time	tSODD	-	100	
Serial output data hold time	tSODH	5	-	

c. Reset Timing Characteristics




***NOTE.** Reset low pulse width shorter than 1us do not make reset. It means undesired short pulse such as glitch, bouncing noise or electorstatic discharge do not cause irregular system reset. Please refer to the table below.

(T_A = -40 to +85°C)


Characteristic	Symbol	Min	Max	Unit
Reset low pulse width	tRES	10	-	us

Table 1. Reset Operation regarding tRES Pulse Width

tRES Pulse	Action
Shorter than 2 us	No reset
Longer than 10 us	Reset
Between 2 us and 10 us	Not determined



AC Characteristics(SPI Mode)



AC Characteristics(RESET timing)

8. Command List & Instruction Descriptions

8.1 Command List


Refer to the Appendix 1: Driver IC Specification

8.2 Instruction Descriptions

Refer to the Appendix 1: Driver IC Specification

9. Power On/Off Sequence

The power on/off sequence should be as the below.




Note 1. VCI, AVDD, VGH and VGL could be turned on/off at the same time within the designated period(5ms).

Note 2. RESETB timing should be observed for the stable operation of the driver.

Note 3. During the Screen save mode or the Power save mode or the Sleep mode, all of the power to the LCD Module should not be supplied.

The Power on/off sequence should be same as the described above while mode is changed to prevent damage of the LCD Panel.

9.1 Power On Sequence



< Note (1) >

- Register 'R02' determines Data format

(R02H)

IB15	IB14	IB13	IB12	IB11	IB10	IB9	IB8	IB7	IB6	IB5	IB4	IB3	IB2	IB1	IB0
0	0	0	0	0	0	1	0	DF1	DF0	0	0	0	1	0	0

- DF Bits Setting

DF1	DF0	Data Format	R02H
0	0	RGB RGB	0204
0	1	RGBX RGBX	0244
1	0	XRGB XRGB	0284
1	1	Setting Inhibited	

< Note (2) >

- Register 'R06', 'R07' determine Vsync Backporch('R06') & Hsync Backporch period('R07')
- Backporch limit
 - (1) $7\text{clk} < \text{Hsync Backporch} < 1024\text{clk}$
 - (2) $3\text{line} < \text{Vsync Backporch} < 512\text{line}$


(R06H)

IB15	IB14	IB13	IB12	IB11	IB10	IB9	IB8	IB7	IB6	IB5	IB4	IB3	IB2	IB1	IB0
0	0	0	0	0	0	0	VBP8	VBP7	VBP6	VBP5	VBP4	VBP3	VBP2	VBP1	VBP0

(R07H)

IB15	IB14	IB13	IB12	IB11	IB10	IB9	IB8	IB7	IB6	IB5	IB4	IB3	IB2	IB1	IB0
0	0	0	0	0	0	0	HBP8	HBP7	HBP6	HBP5	HBP4	HBP3	HBP2	HBP1	HBP0

9.2 Power Off Sequence




10. Reliability Test Result

10.1 Condition


ITEM	CONDITION	REMARK	Test Result
High Temperature Operating Life-test	60°C, 240HR		PASS
Low Temperature Operating Life-test	-20°C, 240HR		PASS
Temperature Humidity Bias test	50°C 90%RH, 240HR		PASS
Temperature Cycle ON/OFF test	-30°C ⇔ 70°C ON/OFF, 5CY	Note(1)	PASS
High Temperature Storage test	70°C, 240HR		PASS
Low Temperature Storage test	-30°C, 240HR		PASS
Wet High Temperature Storage test	60°C 90%RH, 240HR		PASS
Thermal Shock test	-30°C ⇔ 70°C, 100CY	Note(2)	PASS
Electro-Static Discharge test	CONTACT: ±4 kV, 20times A I R: ±8 kV, 20times	Note(3)	PASS
Box Vibration test	RANDOM 0.74Grms, 1HR/Y axis(SMALL BOX)	Note(4)	PASS
Box Drop test	1 Corner 3 Edges 6 faces, 66cm(MEDIUM BOX)		PASS

Note(1) ON Time over 10 seconds, OFF Time under 10 seconds



Temperature Cycle Transit Condition

Note(2) STORAGE



Note(3) Main-LCD, 5 times to every 4 corners of active area

Note(4) Basic transportation by common carrier environmental,
514.4 MIL-STD-810E

OVERALL L RMS LEVEL	BREAK POINT					
	FRQUEN CY	PSD VALUE	FRQUEN CY	PSD VALUE	FRQUEN CY	PSD VALUE
0.74G	10Hz	0.00650	121Hz	0.00300	340Hz	0.00003
	20Hz	0.00650	200Hz	0.00300	500Hz	0.00015
	120Hz	0.00020	240Hz	0.00150	-	-


10.2 Judgement

- > Main LCD should work under the normal condition.
- > After the temperature and humidity test, the luminance and CR(Contrast Ratio) should not be changed over 50% compared with those before the test.

1	PIN NAME
2	LED Cathode
3	LED Cathode
4	LED Anode
5	LED Anode
6	GND
7	X1
8	X2
9	Y2
10	GND
11	C6
12	C5
13	M
14	RESET
15	CS
16	SCL
17	SDI
18	DAT0
19	DAT1
20	DAT2
21	DAT3
22	DAT4
23	DAT5
24	DAT6
25	DAT7
26	DAT8
27	DAT9
28	DAT10
29	DAT11
30	DAT12
31	DAT13
32	DAT14
33	DAT15
34	DAT16
35	DAT17
36	DAT18
37	DAT19
38	DAT20
39	DAT21
40	DAT22
41	DAT23
42	HSYNC
43	VSNC
44	DOTC_K
45	AVDD
46	AVDD
47	VDD
48	VDD
49	C4
50	VGL
51	VGL
52	C3
53	VGH
54	C2
55	C1
56	VCOM
57	VCOM
58	GND
59	GND
60	GND


NO	PART NAME	CODE NO	SPECIFICATION	Q'TY	SPEC NO	REMARK

11. Outline Dimension



GENERAL TOLERANCE				REV	DATE	DESCRIPTION OF REVISION				REASON		CHG'D BY	
STEP	LEVEL 1	LEVEL 2	LEVEL 3	UNIT	mm	DRAWN BY	DES'D BY	CHG'D BY	APP'D BY	MODEL NAME			
0 < X ≤ 4	±0.05	±0.1	±0.2	SCALE	1/1					LTV350QV-F0E			
4 < X ≤ 16	±0.08	±0.15	±0.3	TOLERANCE	W/HUM			S.H.LEE	Y.B.CHU				
16 < X ≤ 64	±0.12	±0.25	±0.5	LEVEL 2	06.01.24	06.01.24	06.01.24			PART/SHEET NAME	Outline-Dimension	SHEET 1/1	
64 < X ≤ 256	±0.25	±0.4	±0.8	SAMSUNG ELECTRONICS									
										CODE NO.		VER. 000	

12. Packing



Note (1) Total : Case: Approx. 2.7 Kg

Box: Approx. 14.1 Kg

(2) Size : Case: 490(W) x 342(D) x 58(H)

Box: 505(W) x 355(D) x 312(H)

(3) Place the panels in the tray facing the direction shown in the figure.


(4) Place 5 tray and cover(empty tray) and pads inside the packing-case.

(5) Place 5 packing-case inside the packing-box.(Affix the label)

(6) Seal the packing-box. Affix the label-safety.

13. Marking & Others

(1) Packing case attach



14. General Precautions

14.1 Handling

- (a) When the module is assembled, it should be attached to the system firmly. Be careful not to twist and bend the module.
- (b) Refrain from strong mechanical shock and / or any force to the module. In addition to damage, this may cause improper operation or damage to the module and back-light unit.
- (c) Note that polarizers are very fragile and could be easily damaged. Do not press or scratch the surface harder than a HB pencil lead.
- (d) Wipe off water droplets or oil immediately. If you leave the droplets for a long time, Staining and discoloration may occur.
- (e) If the surface of the polarizer is dirty, clean it using some absorbent cotton or soft cloth.
- (f) The desirable cleaners are water, IPA(Isopropyl Alcohol) or Hexane. Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.
- (g) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, legs or clothes, it must be washed away thoroughly with soap.
- (h) Protect the module from static , it may cause damage to the Integrated Gate Circuit.
- (i) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- (j) Do not disassemble the module.
- (k) Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.
- (l) Pins of I/F connector shall not be touched directly with bare hands

14.2 Storage

- (a) Do not leave the panel in high temperature, and high humidity for a long time. It is highly recommended to store the module with temperature from 0 to 35°C and relative humidity of less than 70%.
- (b) Do not store the TFT-LCD module in direct sunlight.
- (c) The module shall be stored in a dark place. It is prohibited to apply sunlight or fluorescent light during the store.

14.3 Operation

- (a) Do not connect, disconnect the module in the "Power On" condition.
- (b) Power supply should always be turned on/off by the "Power on/off sequence"

14.4 Others

- (a) The Liquid crystal is deteriorated by ultraviolet, do not leave it in direct sunlight and strong ultraviolet ray for many hours.
- (b) Avoid condensation of water. It may result in improper operation or disconnection of electrode.
- (c) Do not exceed the absolute maximum rating value. (the supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on) Otherwise the panel may be damaged.
- (d) If the panel displays the same pattern continuously for a long period of time, it can be the situation when the image "Sticks" to the screen.
- (e) This panel has its circuitry FPC on the bottom side and should be handled carefully in order not to be stressed.
- (f) Avoid shortness between LED soldering pad and TSP soldering pad.