



## DUAL-IN-LINE SOCKETS Shrink DIP Sockets and Strips Solder Tail and Wrapost

Series 117, 127, 217  
227, 317, 327

- High density DIP sockets and strips for devices featuring 1,78 lead spacing.
- Solder tails use MM #1802 receptacles, See page 140 for details. Wraposts use MM # 1702-2 or 1703-3 receptacles, See page 166 for details.
- Receptacles use Hi-Rel, 4-finger #30 contact and 6-finger #43 contact, both rated at 3 amps. See pages 218 & 220.
- Insulators are high temp. thermoplastic.

Total number of pins				Quantity per tube	<span style="border: 1px solid black; border-radius: 50%; padding: 2px;">For Electrical, Mechanical &amp; Environmental Data, See pg. 4</span> <span style="font-size: 1.2em; font-weight: bold;">Ordering Information</span> <span style="border: 1px solid black; border-radius: 50%; padding: 2px; margin-left: 10px;">XX=Plating Code See Below</span>		
	A	B	C		Solder Tail	2 Level Wrapost L = 9,4	3 Level Wrapost L = 12,95
<b>OPEN FRAME DIP SOCKET</b>							
16	14,53	7,62	9,91	35	117-XX-316-41-005000	127-XX-316-41-002000	127-XX-316-41-003000
28	25,2	10,16	12,45	20	117-XX-428-41-005000	127-XX-428-41-002000	127-XX-428-41-003000
30	26,97	10,16	12,45	18	117-XX-430-41-005000	127-XX-430-41-002000	127-XX-430-41-003000
48	42,98	10,16	12,45	12	117-XX-448-41-005000	127-XX-448-41-002000	127-XX-448-41-003000
20	18,08	15,24	17,53	28	117-XX-620-41-005000	127-XX-620-41-002000	127-XX-620-41-003000
28	25,2	15,24	17,53	20	117-XX-628-41-005000	127-XX-628-41-002000	127-XX-628-41-003000
40	35,86	15,24	17,53	14	117-XX-640-41-005000	127-XX-640-41-002000	127-XX-640-41-003000
42	37,64	15,24	17,53	13	117-XX-642-41-005000	127-XX-642-41-002000	127-XX-642-41-003000
48	42,98	15,24	17,53	11	117-XX-648-41-005000	127-XX-648-41-002000	127-XX-648-41-003000
52	46,53	15,24	17,53	11	117-XX-652-41-005000	127-XX-652-41-002000	127-XX-652-41-003000
56	50,1	15,24	17,53	10	117-XX-656-41-005000	127-XX-656-41-002000	127-XX-656-41-003000
64	57,2	15,24	17,53	8	117-XX-664-41-005000	127-XX-664-41-002000	127-XX-664-41-003000
68	60,76	15,24	17,53	8	117-XX-668-41-005000	127-XX-668-41-002000	127-XX-668-41-003000
64	57,2	19,05	21,34	8	117-XX-764-41-005000	127-XX-764-41-002000	127-XX-764-41-003000
<b>CLOSED FRAME DIP SOCKET</b>							
64	57,2	19,05	21,34	8	217-XX-764-41-005000	227-XX-764-41-002000	227-XX-764-41-003000
<b>SINGLE ROW STRIP SOCKET</b>							
					If desired, we will supply any length up to 21 pins.		
21	37,64				317-93-121-41-005000	327-XX-121-41-002000	327-XX-121-41-003000
<span style="border: 1px solid green; padding: 2px;">For RoHS compliance select <span style="color: green;">◇</span> plating code.</span>					SPECIFY PLATING CODE XX=	<b>93</b>	<b>43◇</b>
					Sleeve (Pin)	5,08µm Sn/Pb	5,08µm Sn
					Contact (Clip)	0,76µm Au	0,76µm Au