High Performance BGA Cooling Solutions w/ Thermal Tape Attachment





ATS Part#:

ATS-55375K-C1-R0

Description:

High Performance X-CUT - Heat Sink, T412, BLACK-ANODIZED

Heat Sink Type: Cross-Cut Heat Sink Attachment: Equivalent Part Number: ATS-55375K-C2-R0

THERMAL TAPE

*Image above is for illustration purpose only.

Features & Benefits

- · High efficiency cross-cut fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance .
- Designed specifically for BGAs and other surface mount packages .
- Comes pre-assembled with high performance thermal interface material ٠

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	5.60 °C/W	4.11 °C/W	3.53 °C/W	3.17 °C/W	2.90 °C/W	2.70 °C/W	2.53 °C/W
	Ducted Flow	n/a						

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	37.5 mm	37.5 mm	14.5 mm	mm	T412	BLACK-ANODIZED
Image above is for illustration purpose only.	 Dimension ATS-5537 (Saint Go Thermal p applicatio ATS resent performant ATS certition 	75K-C2-R0 is the ex bain C675). performance data ar n. rves the right to upd nce. fies that this heat sir	height from the botto act heat sink assem e provided for refere late or change its pro	om of the base to the obly with an equivale ence only. Actual pe oducts without notice S-6 and REACH cor able.	nt therma rformance e to impre	al interface material e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA