



MARKING Part Number

PACKAGING Bulk only

INDUCTANCES 5 μ H to 1000 μ H

OPERATING TEMPERATURE RANGE -55°C to +125°C.

CURRENT RATING Based on 50°C maximum temperature range.

Notes: Part Number Description:

- (1) Designates the Amps DC (Example "20A" for 20 amps DC)
- (2) Designates the Inductance nominal. (Example "10" for 10 μ h)
- (3) Polyolefin Shrink tubing on the outside perimeter.

PART NUMBER	INDUCTANCE μ h $\pm 10\%$	DC RESITANCE OHMS MAXIMUM (w)	RATED CURRENT AMPS MAX. (DC)	A MAX	DIMENSIONS B MAX	C +/-0.005
IHCA-2.5A-50	50	0.12	2.5	.475	.800	0.032
IHCA-2.1A-100	100	0.16	2.1	.475	.800	0.032
IHCA-1.8A-250	250	0.28	1.8	.475	1.05	0.032
IHCA-1.6A-500	500	0.42	1.6	.550	1.05	0.032
IHCA-1.4A-1000	1000	0.60	1.4	.550	1.18	0.032
IHCA-3.7A-25	25	0.060	3.7	.500	.800	0.032
IHCA-3.1A-50	50	0.088	3.1	.500	.800	0.032
IHCA-2.7A-100	100	0.12	2.7	.500	.920	0.032
IHCA-2.4A-250	250	0.20	2.4	.600	.920	0.032
IHCA-2.3A-500	500	0.32	2.3	.750	1.05	0.032
IHCA-6.8A-5	5	0.015	6.8	.475	.800	0.032
IHCA-6.1A-10	10	0.021	6.1	.475	.920	0.032
IHCA-4.8-25	25	0.040	4.8	.550	.800	0.032
IHCA-4.3A-50	50	0.050	4.3	.550	.920	0.032
IHCA-4.2A-100	100	0.070	4.2	.550	1.18	0.032
IHCA-9.3A-5	5	0.010	9.3	.475	1.05	0.040
IHCA-8.3A-10	10	0.015	8.3	.475	1.05	0.040
IHCA-6.5A-25	25	0.030	6.5	.700	1.05	0.040
IHCA-6.1A-50	50	0.040	6.1	.700	1.05	0.040
IHCA-5.9A-100	100	0.060	5.9	.700	1.05	0.040