



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. BRASS PER QQ-B-613
3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
4. BERYLLIUM COPPER PER QQ-C-530
5. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
6. TEFLON MIL-P-19468

1. CRIMPED FERRULE
HEX CRIMP SIZE .151"
2. CONTACT PIN TO SOLDER

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
6	FERRULE	COPPER	NOTE 3	1	FR-44/34X7C
5	COVER	NOTE 2	NOTE 3	1	CV-29X05-T
4	RETAINER RING	NOTE 4	NOTE 3	1	MMCX1121A1-5-C
3	CONTACT PIN	NOTE 1	NOTE 5	1	MMCX1112A1-4-B
2	INSULATOR	NOTE 6	NATURAL	1	MMCX1112A1-3T-50-B
1	HOUSING WITH BODY	NOTE 1	NOTE 3	1	MMCX1112A1-1S-23/17-B

DIMENSIONS ARE IN MILLIMETERS	
UNLESS OTHERWISE SPECIFIED TOLERANCES	
0.5-6	= ±0.2
6-30	= ±0.4
30-120	= ±0.6
120-315	= ±1
315-1000	= ±1.6
1000-2000	= ±2.4

PART NO.	
MMCX1112A1-3GT30G-5A-50	
APPROVED	DATE
	10-11-01'
CHECKED	DATE
	10-11-01'
DRAWN	DATE
	10-11-01'
FILE NO.	

Amphenol	
TITLE	
MMCX R/A CRIMP PLUG	
DRAWING NO.	
KJ-MMCX1112A1-3GT30G-316U/D-50	
ITEM NO.	