



Micro Commercial Components

Micro Commercial Components Corp.

Products End of Life Notification

Issue date: Feb-11th-2010

EOL No. #:020910

Last Buy Date :N/A

Description and Purpose:

MCC has undergone a review of its core business and products , and determined to discontinue below products:

Discontinued Devices	Possible Replacements
BZM55C2V0~BZM55C2V2	N/A
BZM55C2V4~BZM55C39	BZT52C2V4S~BZT52C39S
BZM55C43~BZM55C75	N/A
BZT55C2V0~BZT55C2V2	N/A
BZT55C2V4~BZT55C43	BZT52C2V4~BZT52C43
BZT55C47~BZT55C75	N/A
ERD3.3F~ERD75F	N/A
H2-A3~H36-3	N/A
LLUDZS3.6B~LLUDZS36B	N/A
LS5221~LS5267	DL5221~DL5267
LSH2-A3~LSH36-3	N/A
MCL5221~MCL5259	MMXZ5221~MMXZ5259
MCL5260~MCL5267	N/A
MTZJ2.0~MTZJ39	MMTZJ2.0~MMTZJ39
ZY5.1~ZY39	2EZ5.1D5~2EZ39D5
ZY43~ZY51	N/A



Micro Commercial Components
 Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

**ZY5.1
 THRU
 ZY51**

**Silicon
 2.0 Watt
 Zener Diodes**

Features

- Lead Free Finish/RoHS Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)
- Silicon Power Zener Diodes
- 5.1 thru 51 Volt Voltage Range
- Standard Tolerance of Zener Voltage $\pm 5\%$

Mechanical Data

- Plastic Case: DO-41
- Weight Approx: 0.33 g
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL rating 1

Maximum Ratings @ 25°C Unless Otherwise Specified

Power Dissipation	P_{tot}	2.0	Watt
Thermal Resistance Junction to Ambient Air	R_{thJA}	<45	K/W
Thermal Resistance Junction to Terminal	R_{thJT}	<15	K/W
Operation Temperature	T_J	-50°C to +150°C	
Storage Temperature	T_{STG}	-50°C to +175°C	

Note: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

DO-41

DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.160	0.205	4.10	5.20	
B	0.080	0.107	2.00	2.70	Diameter
C	0.028	0.034	0.71	0.86	Diameter
D	1.000	-----	25.40	-----	

ZY5.1 THRU ZY51

Type	Zener Voltage			Dynamic Resistance		Reverse Current		Z-current
	V _Z (V)		Test Condition	r _d (Ω)	Test Condition	I _R (μA)	Test Condition	I _{Zmax} (mA) @T _a =50°C
	Min	Max	I _Z (mA)	Max	I _Z (mA)	Max	V _R (V)	Max
ZY5.1	4.8	5.4	100	5	100	2	1	333
ZY5.6	5.2	6.0	100	3	100	1	1	300
ZY6.2	5.8	6.6	100	2	100	1	1.5	273
ZY6.8	6.4	7.2	100	2	100	1	2	250
ZY7.5	7.0	7.9	100	2	100	1	2	228
ZY8.2	7.7	8.7	100	2	100	1	3.5	207
ZY9.1	8.5	9.6	50	4	50	1	3.5	188
ZY10	9.4	10.6	50	4	50	1	5	170
ZY11	10.4	11.6	50	6	50	1	5	155
ZY12	11.4	12.7	50	7	50	1	7	142
ZY13	12.4	14.1	50	9	50	1	7	128
ZY15	13.8	15.6	50	10	50	1	10	115
ZY16	15.3	17.1	25	12	25	1	10	105
ZY18	16.8	19.1	25	15	25	1	10	94
ZY20	18.8	21.2	25	15	25	1	10	85
ZY22	20.8	23.3	25	15	25	1	12	77
ZY24	22.8	25.6	25	15	25	1	12	70
ZY27	25.1	28.9	25	15	25	1	14	62
ZY30	28	32	25	15	25	1	14	56
ZY33	31	35	25	15	25	1	17	51
ZY36	34	38	10	30	10	1	17	47
ZY39	37	41	10	40	10	1	20	44
ZY43	40	46	10	40	10	1	20	39
ZY47	44	50	10	40	10	1	24	36
ZY51	48	54	10	60	10	1	24	33



Micro Commercial Components

Ordering Information

Device	Packing
(Part Number)-TP	Tape&Reel; 5Kpcs/Reel
(Part Number)-AP	Ammo Packing;5Kpcs/AmmoBox
(Part Number)-BP	Bulk;1Kpcs/Box

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.