High Power Combiners

3 x 1 High Power Combiners

Specifications

Parameter			
Pump Wavelength Range			800-1000 nm
Number of pump input fibers			3
Input Fiber	Type 1	Core/Clad Diameter	105 /125 μm
		NA	0.15
	Type 2	Core/Clad Diameter	105 /125 μm
		NA	0.22
Output Fiber	Type 1	Core/Clad Diameter	10 /125 μm
		NA	0.08 / 0.46
	Type 2	Core/Clad Diameter	20 / 400 μm
		NA	0.06 / 0.46
Optical Return Loss			≥ 45 dB
Insertion Loss			≤ 0.5 dB
Maximum Total Input Power			21 W
Operating Temperature			0° C ~ + 75° C
Storage Temperature			- 40° C ~ + 85° C
Package Dimensions			75 mm x 12 mm x 8 mm

Note1: All values specified are without connectors and at room temperature.
Note2: Higher performance specifications upon request.

Order Information

M M P C - 3 A - _ - _ - _ - 0

Structure	Input Fiber	Output Fiber	Fiber Length	Connector
3A: 3 x 1	1: Type 1 2: Type 2	1: Type 1 2: Type 2	0: 0.5 meter 1: 1.0 meter 9: 0.75 meter	0: None

www.lighteltech.com
2210 Lind Ave SW, Suite 100
Renton, WA 98057 USA
(425) 277-8000 ph.
(425) 277-5280 Fax

All rights Reserved 2009

LIGHTEL TECHNOLOGIES INC.

ISO 9001:2000