

# BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin



ATS Part#: **ATS024024015-PF-8N**  
 Description: 24.00 x 24.00 x 15.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin



Heat Sink Type: Custom Pin Fin  
 Heat Sink Attachment: N/A  
 Equivalent Part Number: N/A

*\*Image above is for illustration purpose only.*

## Features & Benefits

- High efficiency pin fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

## Thermal Performance

| AIR VELOCITY       |               | @200 LFM<br>1.0 M/S | @300 LFM<br>1.5 M/S | @400 LFM<br>2.0 M/S | @500 LFM<br>2.5 M/S | @600 LFM<br>3.0 M/S | @700 LFM<br>3.5 M/S | @800 LFM<br>4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 6.99 °C/W           | 5.3 °C/W            | 4.5 °C/W            | 4 °C/W              | 3.7 °C/W            | 3.4 °C/W            | 3.2 °C/W            |
|                    | Ducted Flow   | 4.3                 | 3.6                 | 3.2                 | 2.9                 | 2.7                 | 2.6                 | 2.4                 |

## Product Detail

| Schematic Image   | Dimension A | Dimension B | Dimension C | Dimension D | TIM | Finish         |
|---|-------------|-------------|-------------|-------------|-----|----------------|
| <p><i>*Image above is for illustration purpose only.</i></p>  | 24.00 mm    | 24.00 mm    | 15.00 mm    | 24 mm       | N/A | BLACK-ANODIZED |
| <p><b>Notes:</b></p> <ul style="list-style-type: none"> <li>• Dimension <b>A</b> and <b>B</b> refer to component size.</li> <li>• Dimension <b>C</b> is the heat sink height from the bottom of the base to the top of the fin field.</li> <li>• Dimension <b>D</b> is fin tip to fin tip.</li> <li>• Thermal performance data are provided for reference only. Actual performance may vary by application.</li> <li>• ATS reserves the right to update or change its products without notice to improve the design or performance.</li> <li>• ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.</li> <li>• Contact ATS to learn about custom options available.</li> </ul> |             |             |             |             |     |                |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), [sales@qats.com](mailto:sales@qats.com) or [www.qats.com](http://www.qats.com).

© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA

