

5 Watts Power - Wireless System Performance

- 5 Watt Power Performance
- DC - 2.0, DC - 6.0 & DC - 12.4 GHz Model selection
- Rugged Stainless Steel Interface Construction
- Low VSWR - High Performance.

Midwest Microwave's SMA series of medium power fixed coaxial attenuators provide temperature stable, ruggedly built, precision performance in light weight reasonably sized packages. Attenuation values range through 40 dB in 1 dB increments and are available with any combination of female or male SMA connectors



5 Watts Power

Frequency: DC - 2.0, DC-6.0, and DC-12.4 GHz units available

Attenuation Values: 1 thru 20 dB in 1 dB Increments

Attenuation Accuracy: 1- 6 dB ± 0.3 dB

7-10 dB ± 0.5 dB

11-20 dB ± 0.7 dB

VSWR: 1.25 max. @ DC - 6.0 GHz, 1.30 max. @ 6 - 12.4 GHz, and 1.40 max. @ 12.4 - 18.0 GHz

Power: 5 Watts Average @ +40C derated linearly to 0.5 Watts @ +125C

Peak Power: 200 Watts




Operating Temperature Range: -54C to +125C

Finish: Black Anodized Aluminum and Stainless Steel Connectors

DC - 2.0 GHz	481 Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0481-XX-SMA-07	ATT-481F-XX-SMA-07	ATT-481M-XX-SMA-07
XX = Attenuation Value: Select 01-20dB in 1dB increments		
5 WATTS <i>Wireless System Performance</i>		

DC - 6.0 GHz	475 Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0475-XX-SMA-07	ATT-475F-XX-SMA-07	ATT-475M-XX-SMA-07
XX = Attenuation Value: Select 01-20dB in 1dB increments		
5 WATTS <i>Wireless System Performance</i>		

DC - 12.4 GHz	474 Series	Model Numbers
Male/Female	Female/Female	Male/Male
ATT-0474-XX-SMA-07	ATT-474F-XX-SMA-07	ATT-474M-XX-SMA-07
XX = Attenuation Value: Select 01-20dB in 1dB increments		
5 WATTS <i>Wireless System Performance</i>		




[Shopping Cart](#)
[Order Status](#)
[Help Desk](#)
[About Midwest](#)
[Contact Midwest](#)
[Authorized Distributors & Sales Representatives](#)
[Distributors Only](#)
[Customer Login](#) United States

[Try our New Search!](#)

[< Return to Product Categories](#)

SKU	Product	Frequency	Power	Body	Interface	Gender	dB	
Wireless Medium Power SMA Attenuators								
ATT-481M-01-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	1	More Details
ATT-481M-02-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	2	More Details
ATT-481M-03-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	3	More Details
ATT-481M-04-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	4	More Details
ATT-481M-05-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	5	More Details
ATT-481M-06-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	6	More Details
ATT-481M-07-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	7	More Details
ATT-481M-08-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	8	More Details
ATT-481M-09-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	9	More Details
ATT-481M-10-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	10	More Details
ATT-481M-11-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	11	More Details
ATT-481M-12-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	12	More Details
ATT-481M-13-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	13	More Details
ATT-481M-14-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	14	More Details
ATT-481M-15-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	15	More Details

We also have

Attenuator

[BUY NOW](#) Our Price: **\$222.00**


ATT-0640-06-29M-02
6 dB DC-40 Ghz Attenuator
Subminiature Minipad
2.9mm/2.9mm 1 watt
Passivated

[Click for More Info](#)

Connector

[BUY NOW](#) Our Price: **\$32.10**


SMM-1196-59-000-00
Female SMM Gold
Connector Microminiature
Flexible Crimp Contact
RG196 cable

[Click for More Info](#)

ATT-481M-16-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	16	More Details
ATT-481M-17-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	17	More Details
ATT-481M-18-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	18	More Details
ATT-481M-19-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	19	More Details
ATT-481M-20-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	20	More Details
ATT-481M-21-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	21	More Details
ATT-481M-22-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	22	More Details
ATT-481M-23-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	23	More Details
ATT-481M-24-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	24	More Details
ATT-481M-25-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	25	More Details
ATT-481M-26-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	26	More Details
ATT-481M-27-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	27	More Details
ATT-481M-28-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	28	More Details
ATT-481M-29-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	29	More Details
ATT-481M-30-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	30	More Details
ATT-481M-31-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	31	More Details
ATT-481M-32-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	32	More Details
ATT-481M-33-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	33	More Details
ATT-481M-34-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	34	More Details
ATT-481M-35-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	35	More Details

ATT-481M-36-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	36	More Details
ATT-481M-37-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	37	More Details
ATT-481M-38-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	38	More Details
ATT-481M-39-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	39	More Details
ATT-481M-40-SMA-07	Attenuator	2	5	STD	SMA/SMA	M/M	40	More Details

All rights reserved. ©2002 Midwest Microwave